0 NI -	Description	1114	Rat	e (Rs.)	Ref. Tech
Sr. No.	Description	Unit		Composite	Specs.
11-1	Providing and laying sundried clay bricks set in mud mortar including scaffolding in foundation and substructure				11.7.2 (i) 11.17
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	2,350.00 66.55	11,719.68 331.90	
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	5,909.70 167.35	11,585.48 328.10	
11-2	Providing and laying first class solid burnt brick masonry set in mud mortar including and raking out joints in foundation and substructure				11.4.1 11.7.2(i)
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,842.65 52.20	13,080.80 370.45	11.7.4
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,367.65 38.75	11,819.55 334.75	
11-3	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation and substructure				11.4.1 11.7.2(ii)
					11.7.4
	Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cu.m. Cu.ft.	1,842.65 52.20	14,666.25 415.35	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	1,842.65 52.20	14,147.56 400.65	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	1,842.65 52.20	13,608.37 385.40	
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	1,842.65 52.20	13,142.33 372.20	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	1,842.65 52.20	12,764.02 361.50	
vi	Cement sand 1 : 7	Cu.m. Cu.ft.	1,842.65 52.20	12,387.64 350.85	
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	1,842.65 52.20	12,014.24 340.25	
b)	Above 4.5" (115mm) nominal thick brickwork				

Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech.
5r. NO.	Description	Unit	Labour	Composite	Specs.
		•			
i)	Cement sand 1 : 2	Cu.m.	1,367.65		
		Cu.ft.	38.75	399.65	
ii)	Cement sand 1 : 3	Cu.m.	1,367.65	13,521.71	
")	Cement sand 1.5	Cu.ft.	38.75	382.95	
		Cu.n.	30.75	302.95	
iii)	Cement sand 1:4	Cu.m.	1,367.65	12,866.43	
,		Cu.ft.	38.75	364.40	
iv	Cement sand 1 : 5	Cu.m.	1,367.65		
		Cu.ft.	38.75	348.90	
V)	Cement sand 1 : 6	Cu.m.	1,367.65	11,855.68	
•)		Cu.ft.	38.75	335.75	
vi	Cement sand 1:7	Cu.m.	1,367.65	11,466.93	
•		Cu.ft.	38.75	324.75	
	(*) [22]	Ou.n.	00.70	024.70	
vii	Cement sand 1 : 8	Cu.m.	1,367.65	11,055.60	
	Con the second	Cu.ft.	38.75	313.10	
	E				
11-4	Extra for providing and laying first class burnt brick				11.80
	masonry for arches of any kind of wall including				
	scaffolding, formwork and its removal, raking out joints				
	and curing in basement etc.				
ລ)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	981.96	3,498.21	
a)	Opto 4.3 (113 mm) hommal thick block work	Cu.ft.	26.70	88.75	
		Gu.n.	20.70	00.75	
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	943.53	3,133.25	
		Cu.ft.	27.80	99.05	
11-5	Extra for providing and laying first class tile masonry				11.80
	for arches of any kind of walls including scaffolding,				11.90
	formwork and its removal, raking out joints and curing in foundations, basement and plinth.				
اد	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,435.27	4,012.47	
a)		Cu.ft.	40.65	4,012.47	
		Gu.n.	-10.00	110.00	
b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,356.10	3,654.82	
,		Cu.ft.	38.40	103.50	
11-6	Extra for every additional 6 ft (2 m) or part thereof in	Cu.m.	329.40	329.40	11.7.4
	foundation and basement masonry deeper than 6 ft (2	Cu.ft.	9.35	9.35	
11-7	Extra for every additional 5 ft (1.5 m) or part thereof in		245.00	245.00	11.7.4
	plinth higher than 5 ft (1.5m)	Cu.ft.	6.95	6.95	

0	Description	11	Rate (Rs.)		Ref. Tec	
Sr. No.	Description	Unit		Composite	Specs.	
11-8	Extra for every additional 6 ft (2m) or part thereof for arch brick or tile masonry in foundation and basement masonry deeper than 6ft (2m)		329.40 9.35	378.80 10.75	11.80 11.90	
11-9	Extra for every additional 5 ft (1.5m) or part thereof for arch brick or tile masonry in plinth higher than 5ft (1.5m)		245.00 6.95	281.75 8.00	11.80 11.90	
1-10	Providing and laying sundried clay bricks set in mud mortar including scaffolding in ground floor superstructure				11.7.2(i) 11.18	
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,465.52 41.50	11,407.06 323.05		
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,650.00 46.75	6,773.56 191.85		
1-11	Providing and laying first class solid burnt brick masonry set in mud mortar including scaffolding, raking out joints and curing in ground floor				11.4.1 11.7.2(i) 11.7.4	
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	2,292.65 64.95	13,830.65 391.70		
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,698.74 48.10	8,000.78 226.60		
1-12	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in ground floor superstructure				11.4.1 11.7.2(iij 11.7.4	
	Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cu.m. Cu.ft.	2,292.65 64.95	15,370.08 435.30	11.7.4	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,292.65 64.95	14,845.19 420.40		
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,292.65 64.95	14,298.32 404.95		
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	2,292.65 64.95	13,830.00 391.65		
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,292.65 64.95	13,469.66 381.45		

<b>A</b> N	Description		Rat	Ref. Tec	
Sr. No.	Description	Unit	Labour	Composite	Specs.
vi	Cement sand 1 : 7	Cu.m.	2,292.65	13,094.38	
		Cu.ft.	64.95	370.85	
		•			
vii	Cement sand 1 : 8	Cu.m.	2,292.65		
		Cu.ft.	64.95	360.40	
b)	Above 4.5" (115mm) nominal thick brickwork				
	Cement sand 1 : 2	Cu.m.	1,817.65	14,722.90	
		Cu.ft.	51.50	416.95	
ii)	Cement sand 1 : 3	Cu.m.	1,817.65		
		Cu.ft.	51.50	400.15	
iii)	Cement sand 1 : 4	Cu.m.	1,817.65	13,468.48	
,		Cu.ft.	51.50	381.45	
	(x) alla				
iv	Cement sand 1:5	Cu.m.	1,817.65	12,950.46	
		Cu.ft.	51.50	366.75	
	Contraction of the second	•			
v)	Cement sand 1:6	Cu.m.	1,817.65		
	JAMMU & KASHIM	Cu.ft.	51.50	353.35	
vi	Cement sand 1:7	Cu.m.	1,817.65	12,100.57	
		Cu.ft.	51.50	342.70	
vii	Cement sand 1 : 8	Cu.m.	1,817.65	-	
		Cu.ft.	51.50	331.95	
1-13	Extra for providing and laying first class burnt brick				11.80
	masonry for arches of any kind of wall including				
	scaffolding, formwork and its removal, raking out joints				
	and curing in ground floor superstructures.				
- )		0	004.00	0.050.50	
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	334.80 9.50	2,850.52 80.75	
		Gu.n.	9.50	00.75	
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	293.30	2,657.54	
,		Cu.ft.	8.30	75.25	
1-14	Extra for providing and laying first class tile masonry				11.80
	for arches of any kind of walls including scaffolding, formwork and its removal, raking out joints and curing				11.90
	in ground floor superstructures.				
a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	4,093.30	6,926.38	
'	· · · · · · ·	Cu.ft.	115.90	171.50	

Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech	
5r. NO.	Description	Unit	Labour	Composite	Specs.	
b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	3,618.30 102.45	6,055.86 196.15		
11-15	Extra for masonry in pillars and columns in foundation				11.18	
a)	Rectangular or square shape	Cu.m. Cu.ft.	1,255.80 35.55	1,708.82 48.40		
b)	Round shape	Cu.m. Cu.ft.	2,787.05 78.95	3,430.50 97.15		
11-16	Extra for masonry in pillars and cloumns in ground floor superstructure				11.7.4	
a)	Rectangular or square shape	Cu.m. Cu.ft.	1,343.00 38.05	2,546.10 72.10		
b)	Round shape	Cu.m. Cu.ft.	2,596.72 73.55	4,879.67 138.20		
11-17	Extra for masonry of any description in steps.	Cu.m. Cu.ft.	805.46 22.80	805.46 22.80	11.17.4	
11-18	Extra for masonry of any description for bonding old and new masonry including making recesses as required (New masonry inserted in old masonry to be measured)	Cu.ft.	330.85 9.35	473.15 13.40	11.11	
11-19	Providing and laying first class burnt brick honey comb masonry including scaffolding, raking out joints where required and curing in ground floor superstructure (opening not to be deducted for the purpose of measurement).				11.10	
-	Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cu.m. Cu.ft.	1,436.70 40.70	11,816.70 334.65		
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	1,436.70 40.70	11,676.35 330.70		
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	1,436.70 40.70	11,503.10 325.75		
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	1,436.70 40.70	11,402.05 322.90		

Cr Na	Description	110:4	Rat	e (Rs.)	Ref. Tech	
Sr. No.	Description	Unit	Labour	Composite	Specs.	
v)	Cement sand 1 : 6	Cu.m.	1,436.70	11,329.90		
		Cu.ft.	40.70	320.85		
vi	Cement sand 1 : 7	Cu.m.	1,436.70	11,286.60		
•		Cu.ft.	40.70	319.65		
vii	Cement sand 1:8	Cu.m.	1,436.70	11,243.25		
		Cu.ft.	40.70	318.40		
b)	Above 4.5" (115mm) nominal thick brickwork					
i)	Cement sand 1:2	Cu.m.	1,405.45	6,543.55		
-		Cu.ft.	39.80	185.30		
ii)	Cement sand 1:3	Cu.m.	1,405.45	6,238.29		
		Cu.ft.	39.80	176.65		
		0	4 405 15			
III)	Cement sand 1:4	Cu.m.	1,405.45	5,955.97		
		Cu.ft.	39.80	168.70		
iv	Cement sand 1:5	Cu.m.	1,405.45	5,708.76		
IV	7.00	Cu.ft.	39.80	161.70		
	Compet sand 1 : 6	Gu.n.	55.00	101.70		
V)	Cement sand 1 : 6	Cu.m.	1,405.45	5,443.33		
- ,		Cu.ft.	39.80	154.15		
vi	Cement sand 1 : 7	Cu.m.	1,405.45	5,255.51		
		Cu.ft.	39.80	148.85		
		_				
vii	Cement sand 1 : 8		1,405.45	-		
		Cu.ft.	39.80	142.65		
1-20	Extra for providing and laying first class burnt brick				11.12	
1-20	masonry architrave of required shape of any kind of				11.12	
	walls including cutting bricks to required shape,					
	scaffolding, raking out joints and curing in ground floor					
	superstructure.					
<b>c</b> \	Lipto 0" (220 mm) pominal thick brick work	Cu ~~	1 900 00	1 522 40		
a)	Upto 9" (230 mm) nominal thick brick work	Cu.m. Cu.ft.	1,888.90 53.50	4,522.40 128.10		
		Gu.n.	00.00	120.10		
b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	1,058.09	2,698.27		
		Cu.ft.	29.95	76.40		
				-		
1-21	Extra for providing and laying first class burnt tile				11.80	
	masonry architrave of required shape of any kind of				11.12	
	walls including cutting tiles to required shape,					
	scaffolding, raking out joints and curing in ground floor					

Sr. No.	Description	Unit		e (Rs.)	Ref. Tech.
51. NO.	Description	Unit	Labour	Composite	Specs.
a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	2,137.70 60.55	3,768.07 106.70	
b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,974.09 55.90	3,358.64 95.10	
11-22	Extra for providing and laying first class burnt brick masonry coping of required shape any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
a)	Upto 9" (230 mm) nominal thick brick work	Cu.m. Cu.ft.	1,099.50 31.15	3,026.60 85.70	
	Above 13.5" (345 mm) nominal thick brick work	Cu.m. Cu.ft.	1,010.56 28.60	2,551.60 72.25	
11-23	Extra for providing and laying first class burnt tile masonry coping of required shape any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,855.00 52.55	8,002.39 226.65	
b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,730.63 49.00	7,302.29 206.80	
11-24	Extra for providing and laying first class burnt brick masonry cornice, moulding, string course and drip course of required shape in any kind of walls including cutting of bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.12
a)	Upto 9" (230 mm) nominal thick brick work	Cu.m. Cu.ft.	871.59 24.70	1,830.34 51.85	
b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m. Cu.ft.	5,882.01 166.60	1,711.13 48.45	
11-25	Extra for providing and laying first class burnt tile masonry cornice, moulding, barges, string course and drip course of required shape in any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.17
a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,855.00 52.55	5,888.02 166.75	

				Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
						•
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,225.95	4,854.78	
			Cu.ft.	34.70	137.50	
11-26	a)	Extra for brick masonry in first floor	Cu.m.	650.65	670.15	11.17
	,	,	Cu.ft.	18.45	19.00	
	b)	Extra for brick or tile masonry in every additional floor	Cu.m.	392.95	404.75	
		over first floor.				
			0 "	44.45	44.45	
			Cu.ft.	11.15	11.45	
44.07	- )	Enter familiation (the second and the familiar form		040.40	007.05	44 47
11-27	a)	Extra for brick or tile masonry arches in first floor.	Cu.m.	819.40	937.35	11.17
			Cu.ft.	23.20	26.55	
	1.5			504 70	0.40,000	44 47
	D)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	561.70	642.60	11.17
		(N)	Cu.ft.	15.90	18.20	
		A Start Start				
11-28	a)	Extra for honey comb masonry in first floor	Cu.m.	481.90	496.35	11.10
		Extra for honey comb masonry in first floor	Cu.ft.	13.65	14.05	
	b)	Extra for honey comb masonry in every additional floor	Cu.m.	392.95	404.75	
		over first floor.				
			Cu.ft.	11.15	11.45	
11-29		Providing and laying first class brick masonry in				11.70
		steining of walls including scaffolding and curing upto				
		10 ft (3 m) depth.				
	a)	Upto 13.5" (345 mm) nominal thick brick masonry				
	i)	Cement sand 1 : 2	Cu.m.	2,373.90	11,794.13	
			Cu.ft.	67.25	334.00	
	ii)	Cement sand 1 : 3	Cu.m.	2,373.90	11,396.79	
			Cu.ft.	67.25	322.75	
	iii)	Cement sand 1 : 4	Cu.m.	2,373.90	11,031.06	
			Cu.ft.	67.25	312.40	
	iv	Cement sand 1 : 5	Cu.m.	2,373.90	10,633.32	
			Cu.ft.	67.25	301.15	
	v)	Cement sand 1 : 6	Cu.m.	2,373.90	10,237.27	
	v)	Cement sand 1 : 6		2,373.90 67.25	10,237.27 289.95	
	,	Cement sand 1 : 6 Cement sand 1 : 7	Cu.m.			

C. N-	Description	Unit	Rat	e (Rs.)	Ref. Tech	
Sr. No.	Description	Unit	Labour	Composite	Specs.	
vii	Cement sand 1 : 8	Cu.m.	2,373.90	9,947.07		
•		Cu.ft.	67.25	281.70		
		••••	01.20			
b)	Above 13.5" (345 mm) nominal thick brick masonry					
i)	Cement sand 1 : 2	Cu.m.	1,811.40	10,654.90		
		Cu.ft.	51.30	301.75		
::)	Cement sand 1 : 3	Cu.m.	1,811.40	10,387.03		
")		Cu.ft.	51.30	294.15		
		Gu.n.	51.50	234.13		
iii)	Cement sand 1 : 4	Cu.m.	1,811.40	10,120.59		
		Cu.ft.	51.30	286.60		
		0		0.007.1-		
iv	Cement sand 1:5	Cu.m.	1,811.40	9,965.17		
	(*) 522	Cu.ft.	51.30	282.20		
V)	Cement sand 1:6	Cu.m.	1,811.40	9,854.14		
,	Car and	Cu.ft.	51.30	279.05		
	Rep. State					
vi	Cement sand 1 : 7	Cu.m.	1,811.40	9,787.52		
		Cu.ft.	51.30	277.20		
vii	Cement sand 1 : 8	Cu.m.	1,811.40	9,720.93		
•		Cu.ft.	51.30	275.30		
c)	Extra for every additional 5 ft (1.5 m) depth or part	Cu.m.	301.25	310.30		
	thereof for brick masonry in steining of walls.	Cu.ft.	8.55	8.80		
1-30	Providing and laying first class burnt brick masonry				11.14	
	cavity walls bonded with wall ties of approved design					
	at required horizontal and vertical spacings including					
	scaffolding, raking out joints and curing in ground floor superstructure but excluding the cost of wall ties (No					
	deduction will be made from the measurement for					
	cavity in the wall).					
a)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5"					
i)	(115 mm) wall width on either side. Cement sand 1 : 2	Cu.m.	2,885.95	13,785.70		
1)		Cu.ft.	2,885.95	390.40		
				000110		
ii)	Cement sand 1 : 3	Cu.m.	2,885.95	13,573.85		
		Cu.ft.	81.75	384.40		
		0	0.007.0-	10.040.05		
iii)	Cement sand 1 : 4	Cu.m.	2,885.95	13,312.35		
		Cu.ft.	81.75	377.00		

0	Description	11	Rat	e (Rs.)	Ref. Tecl	
Sr. No.	Description	Unit	Labour	Composite	Specs.	
i. /	Compart agend 1 + 5	C., m	2 995 05	12 150 75		
IV	Cement sand 1 : 5	Cu.m.	2,885.95	13,159.75		
		Cu.ft.	81.75	372.70		
V)	Cement sand 1 : 6	Cu.m.	2,885.95	13,050.80		
,		Cu.ft.	81.75	369.60		
vi	Cement sand 1 : 7	Cu.m.	2,885.95			
		Cu.ft.	81.75	367.75		
vii	Cement sand 1 : 8	Cu.m.	2,885.95	12,920.05		
		Cu.ft.	81.75	365.90		
b)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm) wall width on one side and 9" (230 mm) wall					
	width on the other side.					
:)		C., m	2 060 05	14 704 05		
1)	Cement sand 1:2	Cu.m. Cu.ft.	3,060.95 86.70	14,794.05 419.00		
	Care of the second seco	Ou.n.	00.70	410.00		
ii)	Cement sand 1:3	Cu.m.	3,060.95	14,532.70		
	Cement sand 1:3	Cu.ft.	86.70	411.55		
iii)	Cement sand 1 : 4	Cu.m.	3,060.95	14,210.00		
,		Cu.ft.	86.70	402.45		
iv	Cement sand 1 : 5	Cu.m.	3,060.95	14,021.75		
		Cu.ft.	86.70	397.10		
V)	Cement sand 1 : 6	Cu.m.	3,060.95	13,887.25		
- /		Cu.ft.	86.70	393.30		
vi	Cement sand 1 : 7	Cu.m.	3,060.95			
		Cu.ft.	86.70	391.00		
vii	Cement sand 1 : 8	Cu.m.	3,060.95	13,725.90		
		Cu.ft.	86.70	388.75		
c)	2" to 3" (50 mm to 75 mm) nominal cavity and 9" (230					
	mm) wall width on either side.					
i)	Cement sand 1 : 2	Cu.m.	2,735.95	15,029.85		
		Cu.ft.	77.50	425.65		
ii)	Cement sand 1 : 3	Cu.m.	2,735.95	14,653.25		
,		Cu.ft.	77.50	415.00		
iii)	Cement sand 1 : 4	Cu.m.	2,735.95			
		Cu.ft.	77.50	401.80		

Cr. No	Description		Rate (Rs.)		Ref. Tec	
Sr. No.	Description	Unit	Labour	Composite		
i	Compart could 1 - E	C	0 705 05	40.047.40		
IV	Cement sand 1 : 5	Cu.m.	2,735.95			
		Cu.ft.	77.50	394.15		
v)	Cement sand 1 : 6	Cu.m.	2,735.95	13,723.35		
		Cu.ft.	77.50	388.65		
vi	Cement sand 1 : 7	Cu.m.	2,735.95	13,607.15		
VI		Cu.m. Cu.ft.	77.50	385.35		
		Cu.n.	77.50	303.30		
vii	Cement sand 1 : 8	Cu.m.	2,735.95	13,490.90		
		Cu.ft.	77.50	382.05		
d)	2" to 3" (50mm to 75mm) nominal cavity and 4.5"					
u)	(115mm) wall width on one side and 13.5" (345mm)					
	wall width on other side.					
i)	Cement sand 1:2	Cu.m.	2,973.45	-		
	13	Cu.ft.	84.20	429.15		
ii)	Cement sand 1:3	Cu.m.	2,973.45	14,866.25		
"'	TAMMU & KASHIN	Cu.ft.	84.20	421.00		
	AWWU & R					
iii)	Cement sand 1 : 4	Cu.m.	2,973.45	14,510.95		
		Cu.ft.	84.20	410.95		
iv	Cement sand 1 : 5	Cu.m.	2,973.45	14,303.65		
		Cu.ft.	84.20	405.10		
		_				
v)	Cement sand 1 : 6	Cu.m.	2,973.45			
		Cu.ft.	84.20	400.90		
vi	Cement sand 1 : 7	Cu.m.	2,973.45	14,066.75		
		Cu.ft.	84.20	398.40		
:	Cement sand 1 : 8	C	2 072 45	12 077 05		
VII		Cu.m. Cu.ft.	2,973.45 84.20	13,977.95 395.85		
		Cu.n.	04.20	395.65		
e)	Extra for brick masonry in cavity walls in first floor	Cu.m.	737.95	745.35		
		Cu.ft.	20.90	21.10		
ſ	Extra for brick measure in positive wells in a	<b>C</b>	474 40	475.00		
ť)	Extra for brick masonry in cavity walls in every additional floor above first floor	Cu.m. Cu.ft.	471.10 13.35	475.80 13.45		
		Gu.II.	13.35	13.40		
1-31	Providing and laying first class hollow burnt brick				11.70	
	masonry in walls including scaffolding, raking out				11.10	
	joints and curing in ground floor superstructure.					

Sr. No.	Description	11	Rate (Rs.)		Ref. Tech	
5r. NO.	Description	Unit	Labour	Composite	Specs.	
	Upto 4.5" (115 mm) nominal thick brick work					
	Cement sand 1 : 2	Cum	2 270 40	17 506 05		
1)	Cement sand 1.2	Cu.m. Cu.ft.	2,379.40 67.40	17,506.95 495.80		
		Cu.n.	67.40	495.60		
ii)	Cement sand 1:3	Cu.m.	2,379.40	15,788.85		
,		Cu.ft.	67.40	447.15		
			0.070.40	45 000 55		
III)	Cement sand 1:4		2,379.40	15,628.55		
		Cu.ft.	67.40	442.60		
iv	Cement sand 1:5	Cu.m.	2,379.40	15,535.05		
		Cu.ft.	67.40	439.95		
V)	Cement sand 1 : 6	Cu.m.	2,379.40	15,468.25		
	*	Cu.ft.	67.40	438.05		
Vİ	Cement sand 1:7		2,379.40	15,428.20		
	The second se	Cu.ft.	67.40	436.95		
vii	Cement sand 1 : 8	Cum	2,379.40	15,388.10		
VII		Cu.ft.	67.40	435.80		
			01.10	100.00		
b)	Above 4.5" (115mm) nominal thick brickwork					
i)	Cement sand 1 : 2	Cu.m.	2,241.05	16,920.40		
		Cu.ft.	63.45	479.20		
ii)	Cement sand 1:3	Cum	2 2/1 05	15,590.45		
")		Cu.ft.	63.45	441.55		
			00.40	441.00		
iii)	Cement sand 1 : 4	Cu.m.	2,241.05	15,347.15		
		Cu.ft.	63.45	434.65		
iv	Cement sand 1 : 5	Cu.m.	2,241.05	15,205.20		
		Cu.ft.	63.45	430.60		
V)	Cement sand 1:6	Cu.m.	2,241.05	15,103.80		
,		Cu.ft.	63.45	427.75		
vi	Cement sand 1:7		2,241.05	15,042.95		
		Cu.ft.	63.45	426.05		
vii	Cement sand 1:8	Cu.m.	2,241.05	14,982.15		
VII		Cu.ft.	63.45	424.30		
			00.10			
1-32	Providing and laying first class perforated brick	1	1		11.10	

0 N	Description	11	Rate (Rs.)		Ref. Tech	
ir. No.		Unit	Labour	Composite	Specs.	
-	Upto 4.5" (115 mm) nominal thick brick work					
i)	Cement sand 1 : 2	Cu.m.	2,735.42	16,635.05		
		Cu.ft.	77.45	471.10		
ii)	Cement sand 1:3	Cu.m.	2,735.42	15,915.25		
		Cu.ft.	77.45	450.75		
iii)	Cement sand 1:4	Cu.m.	2,735.42	15,668.35		
		Cu.ft.	77.45	443.75		
iv	Cement sand 1:5	Cu.m.	2,735.42	15,524.30		
		Cu.ft.	77.45	439.65		
v)	Cement sand 1 : 6	Cu.m.	2,735.42	15,421.40		
		Cu.ft.	77.45	436.75		
vi	Cement sand 1:7	Cu.m.	2,735.42	15,359.65		
	ERO JAMMU & KASHMA	Cu.ft.	77.45	435.00		
vii	Cement sand 1 : 8	Cu.m.	2,735.42	15,297.95		
		Cu.ft.	77.45	433.25		
b)	Above 4.5" (115mm) nominal thick brickwork					
i)	Cement sand 1 : 2	Cu.m.	2,576.80	16,177.20		
		Cu.ft.	73.00	458.15		
ii)	Cement sand 1 : 3	Cu.m.	2,576.80	15,567.45		
		Cu.ft.	73.00	440.90		
iii)	Cement sand 1:4	Cu.m.	2,576.80	15,212.40		
		Cu.ft.	73.00	430.80		
iv	Cement sand 1 : 5	Cu.m.	2,576.80	15,005.25		
		Cu.ft.	73.00	424.95		
v)	Cement sand 1:6	Cu.m.	2,576.80	14,857.30		
		Cu.ft.	73.00	420.75		
vi	Cement sand 1:7	Cu.m.	2,576.80	14,768.55		
		Cu.ft.	73.00	418.25		
vii	Cement sand 1:8	Cu.m.	2,576.80	14,679.75		
• •		Cu.ft.	73.00	415.75		

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech	
		Unit	Labour	Composite	Specs.	
11-33 a)	Extra for hollow and perforated brick masonry in first	Cu.m.	650.65	670.15		
		Cu.ft.	18.45	19.00		
b)	Extra for hollow and perforated brick masonry in every	Cu.m.	392.95	404.75		
2)	additional floor over first floor.	Cu.ft.	11.15	11.45		
		ount.	11.10	11.10		
11-34	Providing and laying fabric steel reinforcement 1" (25	-	22.05	153.30	11.15	
	mm) wire mesh weighing not less than 2 kg/sq.m. including cutting to required shape and size, overlaps, wastage etc. the reinforcement shall be embeded in every third horizontal course in basement, plinth and ground floor.		10.00	69.55		
11-35	Providing and laying mild steel reinforcement bars in brick work including straightening, removing rust, cutting, bending, wastage, overlaps, placing in position, tying with binding wire (cost of binding wire included) in basement, plinth and ground floor.		9,854.70	90,158.30	11.15	
11-36	Providing and laying hoop iron reinforcement in brick	Kg.	28.55	140.40	11.15	
	work including straightening, cutting, punching, overlaps, wastage and placing in position including anti-corrosive bitumastic paint two coats in basement, plinth and ground floor.	Lb.	12.95	63.70		
11-37	Flat iron wall ties size 8" x 3/4" x 1/4" (200 mm x 20	Kg.	32.50	140.95	11.14.3	
	mm x 5 mm) weighing 39.25 kg per sq.m or 200 mm x 20 mm x 4 mm weighing 31.4 kg./ Sq.m.	Lb.	14.75	63.95		
11-38	Providing and placing mild steel reinforcement bars in steining of brick work in wells. Vertical bars are to be placed in two staggered rows and at 10" (250mm) centered in each row including straightening, removing of rust, cutting, bending, binding, wastage, overlaps, placing in position and tying with binding wire upto 5ft. (1.5m) depth or part thereof.	Ton	1,695.55	83,204.85	11.15	
11-39	Providing and placing hoop iron in steining of brick	Ka	32.15	144.00	11.15	
11-39	work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Kg. Lb.	14.60	65.30	11.10	
11-40 a)	Extra for mild steel bars or hoop iron reinforcement in	Kg.	5.70	6.15	11.15	
/		Lb.	2.60	2.80		
<u>ہ</u>	Providing and placing hoop iron in steining of brick	Kg.	3.45	3.75		
U)	work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	kg. Lb.	3.45 1.55	3.75 1.70		

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech
Sr. NO.	Description	Unit	Labour	Composite	Specs.
11-41	Extra for mild steel or hoop iron reinforcement in steining of brickwork in wells for every additional 5 ft (1.5m) depth or part thereof beyond 5ft (1.5m) depth.	•	6.30 2.85	6.75 3.05	11.15
11-42	Providing and laying fire brick lining in walls for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures				11.19
a)	4.5" (115 mm) nominal thick fire brick lining in walls of	Cu.m. Cu.ft.	4,230.15 119.80	17,940.70 508.10	
b)	9" (230 mm) nominal thick fire brick lining in walls of	Cu.m. Cu.ft.	3,636.40 103.00	12,787.10 362.15	
11-43	Providing and laying fire brick lining in arches for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor				11.19
a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire places.	Cu.m. Cu.ft.	4,823.45 136.60	21,693.40 614.35	
b)	9" (230 mm) nominal thick fire brick lining in arches of fire places.	Cu.m. Cu.ft.	4,229.70 119.80	21,213.25 600.75	
11-44	Providing and laying fire brick lining in walls for fire places laid in vitrified fire clay mortar including scaffolding in basement, plinth and ground floor.				11.19
a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire places.	Cu.m. Cu.ft.	4,230.15 119.80	18,367.15 520.15	
b)	9" (230 mm) nominal thick fire brick lining in walls of fire places.		3,636.40	17,729.60	
		Cu.ft.	103.00	502.10	
11-45	Providing and laying fire brick lining in arches for fire places with vitrified fire clay mortar including scaffolding, formwork and its removal in basement, plinth & ground floor				11.19
a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	4,823.45	19,617.40	
		Cu.ft.	136.60	555.60	

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech	
5r. NO.	Description	Unit	Labour	Composite	Specs.	
b)	9" (230 mm) nominal thick fire brick lining in arches of fire places.		4,229.70			
11-46 a)	Extra for first floor over item 11-42 to 11-45	Cu.ft. Cu.m.	119.80 650.65	535.85 670.15		
		Cu.ft.	18.45	19.00		
b)	Extra for every additional floor above first floor over item 11-46(a)	Cu.m. Cu.ft.	392.95 11.15	404.75 11.45		
11-47	Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in lintel including scaffolding, fromwork and its removal, curing but excluding the cost of reinforcement in basement, plinth and ground floor.	Cu.m. Cu.ft.	2,671.90 75.65	17,813.85 504.50	11.70	
11-48	Providing and laying reinforced first class burnt bricks with cement concrete in ribs and on top using screened graded shingle/bajri 3/4" and down gauge, mix not leaner than 1:2:4 including formwork and its removal, compacting, curing but excluding the cost of reinforcement in basement and ground floor.					
a)	R.B. Slab 4.5" nominal thick including 1.5" thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	3,846.90 108.95	15,477.25 438.30		
b)	R.B. Slab 6" nominal thick including 1.5" (38mm) thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	2,671.90 75.65	13,076.28 370.35		
c)	R.B. Slab 8" nominal thick including 2" thick R.C. ribs, 1.5" thick cover on top and 4 brick panel laid in cement sand mortar 1:3.		2,421.90 68.60	12,117.76 343.20		
11-49	Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in cantilever slab, sun shade etc. including formwork and its removal curing but excluding the cost of reinforcement in basement and ground floor.				11.70	
a)	3" nominal thick cantilever slab and sun shade etc.	Cu.m. Cu.ft.	3,367.31 95.35	22,378.44 633.75		
b)	4.5" (115mm) nominal thick cantilever slab and sun	Cu.m. Cu.ft.	2,834.20 80.25	19,407.68 549.65		

Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech
5r. NO.		Unit	Labour	Composite	Specs.
11-50	Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in stair case waist slab and landing of required section including scaffolding and formwork and its removal, curing but excluding the cost of reinforcement in basement and ground	Cu.m.	3,877.71	21,954.70	11.70
	floor.	Cu.ft.	109.80	621.75	
11-51 a)	Extra for R.B. masonry for first floor.	Cu.m.	317.95	409.38	
		Cu.ft.	9.00	11.60	
b)	Extra for every additional floor above first floor over	Cu.m.	317.95	327.50	
,		Cu.ft.	9.00	9.25	
11-52	Extra labour for profile and flared out walls.	Cu.m. Cu.ft.	517.95 14.65	533.50 15.10	
11-53	Extra labour for pucca brick work in piers and				
a)	Above 10 ft to 20 ft (3 m to 6 m) height 20 ft (3 m to 6 m)	Cu.m. Cu.ft.	402.35 11.40	414.40 11.75	
b)	Above 20 ft (6 m) height	Cu.m. Cu.ft.	749.20 21.20	771.70 21.85	
11-54	Extra to face work 4.5" (115 mm) nominal thick using special bricks instead of first class burnt bricks with proper ancharage, arrangment as directed by Enigneer incharge.	Cu.ft.	127.50 3.60	140.25 3.95	
11-55	Extra for dressing or chamfering bricks.				
a)	Special architectural bricks	% Nos.	862.50	862.50	
b)	All other purposes	% Nos.	431.25	431.25	
11-56	Providing and laying ghilafi brick work 13.5" (345mm) nominal thick including scaffolding and raking out joints with 1:5 mortar				11.20
a)	Foundation, basement and plinth	Cu.m. Cu.ft.	1,740.10 49.30	10,735.70 304.05	
b)	Walls in superstructure	Cu.m. Cu.ft.	1,833.85 51.95	10,829.45 306.70	

	<b>_</b>		Rate (Rs.)	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	•
11-57	Providing and laying first class burnt bricks flooring or pitching dry bricks laid flat.	Cu.m. Cu.ft.	700.00 19.80	13,565.35 384.20	14.80
11-58	Providing pise wall (mud walling) in superstructure.	Cu.m. Cu.ft.	668.75 18.95	16,918.75 479.15	11.7.2(A)
11-59	Cleaning pricks dismantied from kacha pacca	% Nos.	315.00	315.00	4.10
11-60	Scraping bricks dismantled from pacca masonry.	% Nos.	607.50	607.50	
11-61	Supplying and filling sand under floor or plugging in wells.with lead upto 800 ft (250m)	Cu.m. Cu.ft.	259.64 7.35	927.28 26.25	4.10 3.8.5
11-62	Charmening sides of nead regulators to increase	Cu.m. Cu.ft.	831.25 23.55	1,204.71 34.10	
11-63	Replacing Kallar eaten bricks	Each	47.50	79.85	
11-64	Repairing corners of bridges and other hydraulic masonry works.	Each	475.00	1,122.05	
11-65	Extra labour for drains of bath rooms etc.	R.M. R.ft.	118.75 36.20	118.75 36.20	
11-66	Extra work for Marrow corners.	Each	237.50	280.00	11.7.4.4 (c )
11-67	Extra for first class burnt solid or hollow block or tile masonry of any description in any floor or other than building for every 1.50 m. height or part thereof beyond 4.5m.	Cu.ft.	80.20 2.25	94.60 2.70	11.70
11-68	Extra for reinforcement in brick work of any description for every 5 ft 1.5m height or part thereof beyond 15 ft or 4.5m.		1,710.00 1,737.45	1,744.20 1,772.20	5.40