0	Description	11	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
11-1	Providing and laying sundried clay bricks set in mud mortar including scaffolding in foundation and substructure				11.7.2 (i) 11.17
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	2,350.00 66.55	11,719.68 331.90	
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	5,909.70 167.35	11,585.48 328.10	
11-2	Providing and laying first class solid burnt brick masonry set in mud mortar including and raking out joints in foundation and substructure				11.4.1 11.7.2(i)
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,842.65 52.20	11,773.30 333.45	11.7.4
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,367.65 38.75	10,604.55 300.35	
11-3	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation and substructure				11.4.1 11.7.2(ii)
2)	Upto 4.5" (115 mm) nominal thick brick work				11.7.4
	Cement sand 1 : 2	Cu.m. Cu.ft.	1,842.65 52.20	13,380.35 378.95	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	1,842.65 52.20	12,901.12 365.35	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	1,842.65 52.20	12,378.44 350.55	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	1,842.65 52.20	11,936.64 338.05	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	1,842.65 52.20	11,580.39 327.95	
vi)	Cement sand 1 : 7	Cu.m. Cu.ft.	1,842.65 52.20	11,231.47 318.10	
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	1,842.65 52.20	10,885.63 308.30	
	Above 4.5" (115mm) nominal thick brickwork Cement sand 1 : 2	Cu.m. Cu.ft.	1,367.65 38.75	12,934.20 366.30	

Sr. No	•	Depariation	Unit	Rat	e (Rs.)	Ref. Tech.
Sr. No	0.	Description	Unit	Labour	Composite	Specs.
	::\		0	4 007 05	40.000.54	
	11)	Cement sand 1 : 3	Cu.m.	1,367.65	12,389.51	
			Cu.ft.	38.75	350.90	
	iii)	Cement sand 1 : 4	Cu.m.	1,367.65	11,745.33	
	,		Cu.ft.	38.75	332.65	
			ount	00.10	002.00	
1	iv)	Cement sand 1:5	Cu.m.	1,367.65	11,221.06	
l		13	Cu.ft.	38.75	317.80	
1		A A A A A A A A A A A A A A A A A A A				
	v)	Cement sand 1:6	Cu.m.	1,367.65	10,780.18	
		Compete and 1:7	Cu.ft.	38.75	305.30	
	vi)	Cement sand 1:7	Cu.m.	1,367.65	10,416.05	
			Cu.ft.	38.75	295.00	
			_			
	vii	Cement sand 1:8	Cu.m.	1,367.65	10,032.06	
			Cu.ft.	38.75	284.10	
11-4		Extra for providing and laying first class burnt brick masonry				11.80
11 4		for arches of any kind of wall including scaffolding, formwork				11.00
		and its removal, raking out joints and curing in basement etc.				
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	981.96	3,433.48	
			Cu.ft.	26.70	87.85	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	943.53	3,101.96	
			Cu.ft.	27.80	97.25	
11-5		Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork				11.80
		and its removal, raking out joints and curing in foundations,				11.90
		basement and plinth.				
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,435.27	3,742.09	
	/	· · · · · · · · · · · · · · · · · · ·	Cu.ft.	40.65	106.00	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,356.10	3,395.47	
			Cu.ft.	38.40	96.15	
11-6		Extra for every additional 6 ft (2 m) or part thereof in foundation and becoment measure deeper then 6 ft (2 m)		329.40	329.40	11.7.4
		foundation and basement masonry deeper than 6 ft (2 m)	Cu.ft.	9.35	9.35	
44 7			0	045.00	045.00	
11-7		Extra for every additional 5 ft (1.5 m) or part thereof in plinth higher than 5 ft (1.5m)		245.00	245.00	11.7.4
			Cu.ft.	6.95	6.95	
11-8		Extra for every additional 6 ft (2m) or part thereof for arch	Cu.m.	329.40	378.80	11.80
		brick or tile masonry in foundation and basement masonry	Cu.ft.	9.35	10.75	11.90
		deeper than 6ft (2m)		0.00		

Sr. No	<b>`</b>	Description	Unit	Rat	e (Rs.)	Ref. Tech.
51. NC	<i>.</i>	Description	Onit	Labour	Composite	Specs.
11-9		Extra for every additional 5 ft (1.5m) or part thereof for arch	Cu.m.	245.00	281.75	11.80
11-9		brick or tile masonry in plinth higher than 5ft (1.5m)	Cu.m. Cu.ft.	245.00 6.95	8.00	11.80
			Cu.n.	0.95	0.00	11.90
11-10		Providing and laying sundried clay bricks set in mud mortar				11.7.2(i)
11 10		including scaffolding in ground floor superstructure				11.18
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	1,465.52	11,407.06	
		13	Cu.ft.	41.50	323.05	
		A A A A A A A A A A A A A A A A A A A				
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	1,650.00	6,773.56	
		TO JAMMU & KASHM	Cu.ft.	46.75	191.85	
11-11		Providing and laying first class solid burnt brick masonry set in mud mortar including scaffolding, raking out joints and				11.4.1
		curing in ground floor superstructure.				11.7.2(i) 11.7.4
						11.7.4
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	2,292.65	13,830.65	
	u)		Cu.ft.	64.95	391.70	
			•••••	0.000		
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	1,698.74	8,000.78	
	,		Cu.ft.	48.10	226.60	
11-12		Providing and laying first class solid burnt brick masonry				11.4.1
		including scaffolding, raking out joints and curing in ground				11.7.2(ii)
	<b>2</b> )	floor superstructure Upto 4.5" (115 mm) nominal thick brick work				11.7.4
		Cement sand 1 : 2	Cu.m.	2,292.65	14,059.64	11.7.4
	.,		Cu.ft.	64.95	398.20	
			•••••	0.000	000120	
	ii)	Cement sand 1:3	Cu.m.	2,292.65	13,573.82	
	,		Cu.ft.	64.95	384.40	
	iii)	Cement sand 1 : 4	Cu.m.	2,292.65	13,042.74	
			Cu.ft.	64.95	369.40	
	iv)	Cement sand 1 : 5	Cu.m.	2,292.65	12,597.61	
			Cu.ft.	64.95	356.75	
	,					
	V)	Cement sand 1 : 6	Cu.m.	2,292.65	12,256.63	
			Cu.ft.	64.95	347.10	
	, <i>"</i> )	Cement sand 1 : 7	Cu.m.	2,292.65	11,907.69	
	vi)		Cu.m. Cu.ft.	2,292.65 64.95	337.25	
			Gu.II.	04.90	331.23	
	vii	Cement sand 1 : 8	Cu.m.	2,292.65	11,564.78	
	, ,		Cu.ft.	64.95	327.50	
			00.11.	01.00	521.00	

0. 1		Description	11	Rat	e (Rs.)	Ref. Tech.
Sr. No	).	Description	Unit	Labour	Composite	Specs.
	L.)					
		Above 4.5" (115mm) nominal thick brickwork	Cu.m.	1 017 65	12 520 64	
	1)	Cement sand 1:2		1,817.65 51.50	13,530.64	
			Cu.ft.	51.50	383.20	
	ii)	Cement sand 1:3	Cu.m.	1,817.65	12,981.68	
	,		Cu.ft.	51.50	367.65	
		(x) alla				
	iii)	Cement sand 1:4	Cu.m.	1,817.65	12,330.52	
			Cu.ft.	51.50	349.20	
		A State of the second s	_			
	iv)	Cement sand 1:5	Cu.m.	1,817.65	11,830.86	
		Cellen said 1.5	Cu.ft.	51.50	335.05	
	V)	Cement sand 1 : 6	Cu.m.	1,817.65	11,380.05	
	,		Cu.ft.	51.50	322.30	
	vi)	Cement sand 1:7	Cu.m.	1,817.65	11,026.41	
			Cu.ft.	51.50	312.25	
			0	4 9 4 7 9 5	40.070.00	
	VII	Cement sand 1:8	Cu.m. Cu.ft.	1,817.65 51.50	10,670.89 302.20	
			Cu.it.	51.50	302.20	
11-13		Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including scaffolding, formwork				11.80
		and its removal, raking out joints and curing in ground floor superstructures.				
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	334.80	2,712.04	
	ς,		Cu.ft.	9.50	76.80	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	293.30	2,570.87	
			Cu.ft.	8.30	72.80	
		Friday for any difference in the first stars the assessment for				44.00
11-14		Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding, formwork				11.80 11.90
		and its removal, raking out joints and curing in ground floor superstructures.				11.90
	a١	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	4,093.30	6,437.62	
	~,		Cu.ft.	115.90	158.00	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	3,618.30	5,578.12	
			Cu.ft.	102.45	182.30	
11-15		Extra for masonry in pillars and columns in foundation				11.18
	a)	Rectangular or square shape	Cu.m.	1,255.80	1,708.82	
			Cu.ft.	35.55	48.40	

Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech.
SI. NO.	Description	Onic	Labour	Composite	Specs.
b)	Round shape	Cu.m.	2,787.05	3,368.75	
		Cu.ft.	78.95	95.40	
11-16	Extra for masonry in pillars and cloumns in ground floor superstructure				11.7.4
a)	Rectangular or square shape	Cu.m. Cu.ft.	1,343.00 38.05	2,546.10 72.10	
b)	Round shape	Cu.m. Cu.ft.	2,596.72 73.55	4,776.75 135.30	
11-17	Extra for masonry of any description in steps.	Cu.m.	805.46	805.46	11.17.4
1 1-17	Exactor masonry or any description in steps.	Cu.m. Cu.ft.	22.80	22.80	11.17.4
		Ou.it.	22.00	22.00	
11-18	Extra for masonry of any description for bonding old and new masonry including making recesses as required (New masonry inserted in old masonry to be measured)		330.85 9.35	473.15 13.40	11.11
11-19	Providing and laying first class burnt brick honey comb masonry including scaffolding, raking out joints where required and curing in ground floor superstructure (opening not to be deducted for the purpose of measurement).				11.10
a	Upto 4.5" (115 mm) nominal thick brick work				
-	Cement sand 1 : 2	Cu.m.	1,436.70	10,757.20	
		Cu.ft.	40.70	304.65	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	1,436.70 40.70	10,624.75 300.90	
,	Cement sand 1 : 4	Cu.m.	1,436.70	10,443.25	
,		Cu.ft.	40.70	295.75	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	1,436.70 40.70	10,337.40 292.75	
V)	Cement sand 1 : 6	Cu.m. Cu.ft.	1,436.70 40.70	10,261.75 290.60	
vi	Cement sand 1 : 7	Cu.m. Cu.ft.	1,436.70 40.70	10,216.40 289.35	
vi	Cement sand 1 : 8	Cu.m.	1,436.70	10,171.00	
		Cu.ft.	40.70	288.05	
b)	Above 4.5" (115mm) nominal thick brickwork				
i)	Cement sand 1 : 2	Cu.m.	1,405.45	5,971.61	
		Cu.ft.	39.80	169.10	

Sr. No		Description	Unit	Rat	e (Rs.)	Ref. Tech.	
Sr. NO	).	Description	Unit	Labour	Composite	Specs.	
	ii)	Cement sand 1 : 3	Cu.m.	1,405.45	5,690.74		
			Cu.ft.	39.80	161.15		
	iii)	Cement sand 1 : 4	Cu.m.	1,405.45	5,421.34		
	,		Cu.ft.	39.80	153.55		
	iv)	Cement sand 1:5	Cu.m.	1,405.45	5,189.58		
			Cu.ft.	39.80	146.95		
	V)	Cement sand 1:6	Cu.m.	1,405.45	4,943.59		
		Etc. Chanter	Cu.ft.	39.80	140.00		
	vi)	Cement sand 1 : 7	Cu.m.	1,405.45	4,770.28		
	v1)		Cu.m. Cu.ft.	39.80	4,770.28		
			Gu.n.	39.00	155.10		
	vii	Cement sand 1 : 8	Cu.m.	1,405.45	4,569.97		
	•		Cu.ft.	39.80	129.40		
11-20		Extra for providing and laying first class burnt brick masonry architrave of required shape of any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.12	
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m.	1,888.90	4,457.05		
	α)		Cu.ft.	53.50	126.25		
			ound	00.00	120.20		
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	1,058.09	2,654.70		
	,		Cu.ft.	29.95	75.20		
11-21		Extra for providing and laying first class burnt tile masonry				11.80	
		architrave of required shape of any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.12	
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	2,137.70	3,402.87		
	- 7	,	Cu.ft.	60.55	96.35		
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,974.09	2,967.36		
	,		Cu.ft.	55.90	84.05		
11-22		Extra for providing and laying first class burnt brick masonry coping of required shape any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and				11.17	
	a)	curing in ground floor superstructure. Upto 9" (230 mm) nominal thick brick work	Cu.m.	1,099.50	2,993.90		
	,		Cu.ft.	31.15	84.80		
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m.	1,010.56	2,518.90		
			Cu.ft.	28.60	71.35		

Sr. No	n	Description	Unit	Rate (Rs.)		Ref. Tech.
51. NG	υ.	Description	Unit	Labour	Composite	Specs.
11-23	a)	Extra for providing and laying first class burnt tile masonry coping of required shape any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure. Upto 9" (230 mm) nominal thick tile masonry		1,855.00 52.55	8,745.94 247.70	11.17
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,730.63 49.00	8,016.11 227.00	
11-24		Extra for providing and laying first class burnt brick masonry cornice, moulding, string course and drip course of required shape in any kind of walls including cutting of bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.12
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m.	871.59	1,830.34	
			Cu.ft.	24.70	51.85	
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m. Cu.ft.	777.79 22.05	1,711.13 48.45	
11-25		Extra for providing and laying first class burnt tile masonry cornice, moulding, barges, string course and drip course of required shape in any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.17
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,855.00	6,481.71	
			Cu.ft.	52.55	183.55	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,225.95 34.70	5,415.12 153.35	
11-26	a)	Extra for brick masonry in first floor	Cu.m.	650.65	670.15	11.17
			Cu.ft.	18.45	19.00	
	b)	Extra for brick or tile masonry in every additional floor over first floor.		392.95	404.75	
			Cu.ft.	11.15	11.45	
11-27	a)	Extra for brick or tile masonry arches in first floor.	Cu.m. Cu.ft.	819.40 23.20	937.35 26.55	11.17
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	561.70	642.60	11.17
			Cu.ft.	15.90	18.20	
11-28	a)	Extra for honey comb masonry in first floor	Cu.m. Cu.ft.	481.90 13.65	496.35 14.05	11.10
	b)	Extra for honey comb masonry in every additional floor over first floor.	Cu.m.	392.95	404.75	

Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech.
5r. NO.	Description	Unit	Labour	Composite	Specs.
		Cu.ft.	11.15	11.45	
11-29	Providing and laying first class brick masonry in steining of walls including scaffolding and curing upto 10 ft (3 m) depth.				11.70
a)	Upto 13.5" (345 mm) nominal thick brick masonry				
-	Cement sand 1 : 2	Cu.m.	2,373.90	10,827.99	
	(x) pla	Cu.ft.	67.25	306.65	
ii)	Cement sand 1:3	Cu.m.	2,373.90	10,458.47	
	A State of the sta	Cu.ft.	67.25	296.20	
	Es guint	0	0.070.00	40.000.00	
III)	Cement sand 1:4	Cu.m.	2,373.90 67.25	10,093.98	
		Cu.ft.	67.25	285.85	
iv)	Cement sand 1 : 5	Cu.m.	2,373.90	9,713.32	
,		Cu.ft.	67.25	275.10	
V)	Cement sand 1 : 6	Cu.m.	2,373.90	9,339.76	
		Cu.ft.	67.25	264.50	
vi)	Cement sand 1 : 7	Cu.m.	2,373.90	9,325.10	
		Cu.ft.	67.25	264.10	
		0	0.070.00	0.000.00	
VII	Cement sand 1 : 8	Cu.m. Cu.ft.	2,373.90 67.25	9,068.03 256.80	
		Cu.n.	07.25	200.00	
b)	Above 13.5" (345 mm) nominal thick brick masonry				
	Cement sand 1 : 2	Cu.m.	1,811.40	9,797.07	
		Cu.ft.	51.30	277.45	
ii)	Cement sand 1 : 3	Cu.m.	1,811.40	9,547.41	
		Cu.ft.	51.30	270.40	
;;;)	Cement sand 1 : 4	Cu.m.	1,811.40	9,268.24	
III <i>)</i>	Cement sand 1.4	Cu.m. Cu.ft.	51.30	9,200.24 262.50	
		Cu.n.	51.50	202.50	
iv)	Cement sand 1 : 5	Cu.m.	1,811.40	9,105.41	
,		Cu.ft.	51.30	257.85	
V)	Cement sand 1 : 6	Cu.m.	1,811.40	8,989.10	
		Cu.ft.	51.30	254.60	
vi)	Cement sand 1 : 7	Cu.m.	1,811.40	8,919.34	
		Cu.ft.	51.30	252.60	
vii	Cement sand 1 : 8	Cu.m.	1,811.40	8,849.55	
VII		Cu.m. Cu.ft.	51.30	250.60	
		00.11.	01.00	200.00	

0	Description	11	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
c)	Extra for every additional 5 ft (1.5 m) depth or part thereof for	Cu.m.	301.25	310.30	
	brick masonry in steining of walls.	Cu.ft.	8.55	8.80	
11-30	Providing and laying first class burnt brick masonry cavity				11.14
	walls bonded with wall ties of approved design at required				
	horizontal and vertical spacings including scaffolding, raking				
	out joints and curing in ground floor superstructure but excluding the cost of wall ties (No deduction will be made				
	from the measurement for cavity in the wall).				
<i>a)</i>	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm)				
u)	wall width on either side.				
i)	Cement sand 1:2	Cu.m.	2,885.95	12,747.50	
''	Cement sand 1 : 2	Cu.ft.	2,885.95 81.75	361.00	
	AMMU & KA	Cu.n.	01.75	301.00	
ii)	Cement sand 1 : 3	Cu.m.	2,885.95	12,547.50	
")	Cement Sand 1.5	Cu.ft.	81.75	355.35	
		Ou.n.	01.75	000.00	
;;;;)	Cement sand 1 : 4	Cu.m.	2,885.95	12,273.50	
		Cu.ft.	81.75	347.60	
		Cu.n.	01.75	347.00	
iv)	Cement sand 1 : 5	Cu.m.	2,885.95	12,113.70	
10)	Cement Sand 1.5	Cu.ft.	81.75	343.05	
		Ou.n.	01.75	0-0.00	
V)	Cement sand 1 : 6	Cu.m.	2,885.95	11,999.55	
• • •		Cu.ft.	81.75	339.85	
vi)	Cement sand 1 : 7	Cu.m.	2,885.95	11,931.05	
,		Cu.ft.	81.75	337.90	
vii	Cement sand 1:8	Cu.m.	2,885.95	11,862.55	
•		Cu.ft.	81.75	335.95	
b)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm)				
	wall width on one side and 9" (230 mm) wall width on the				
i)	other side. Cement sand 1 : 2	Cu.m.	3,060.95	13,714.95	
.,		Cu.ft.	86.70	388.40	
		•••••	00.10		
ii)	Cement sand 1 : 3	Cu.m.	3,060.95	13,468.15	
,		Cu.ft.	86.70	381.45	
iii)	Cement sand 1 : 4	Cu.m.	3,060.95	13,130.10	
,		Cu.ft.	86.70	371.85	
		-	-	-	
iv)	Cement sand 1 : 5	Cu.m.	3,060.95	12,932.85	
,		Cu.ft.	86.70	366.25	
		-	-	-	
V)	Cement sand 1 : 6	Cu.m.	3,060.95	12,792.00	
,		Cu.ft.	86.70	362.30	
		<b>C</b> 0.10.	00110	002.00	

	<b>D</b>		Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
		_			
vi)	Cement sand 1 : 7	Cu.m.	3,060.95	12,707.50	
		Cu.ft.	86.70	359.90	
vii	Cement sand 1 : 8	Cu.m.	3,060.95	12,622.95	
, vii		Cu.ft.	86.70	357.50	
c)	2" to 3" (50 mm to 75 mm) nominal cavity and 9" (230 mm)				
	wall width on either side.				
i)	Cement sand 1 : 2	Cu.m.	2,735.95	14,017.50	
	Contraction of the second	Cu.ft.	77.50	397.00	
	Cement sand 1:3	0	0 705 05	40.004.05	
II)	Cement sand 1:3	Cu.m.	2,735.95	13,661.95	
		Cu.ft.	77.50	386.90	
iii)	Cement sand 1 : 4	Cu.m.	2,735.95	13,174.85	
,		Cu.ft.	77.50	373.10	
iv)	Cement sand 1 : 5	Cu.m.	2,735.95	12,890.75	
		Cu.ft.	77.50	365.05	
		_			
v)	Cement sand 1 : 6	Cu.m.	2,735.95	12,687.80	
		Cu.ft.	77.50	359.35	
vi)	Cement sand 1 : 7	Cu.m.	2,735.95	12,566.00	
,		Cu.ft.	77.50	355.90	
vii	Cement sand 1 : 8	Cu.m.	2,735.95	12,444.25	
		Cu.ft.	77.50	352.45	
d)	2" to 3" (50mm to 75mm) nominal cavity and 4.5" (115mm)				
	wall width on one side and 13.5" (345mm) wall width on other side.				
i)	Cement sand 1 : 2	Cu.m.	2,973.45	14,052.75	
		Cu.ft.	84.20	398.00	
::\	Cement sand 1 : 3	Cu.m.	2,973.45	13,781.00	
11)	Cement sand 1.3	Cu.m. Cu.ft.	2,973.45 84.20	390.30	
		Gu.n.	04.20	390.30	
iii)	Cement sand 1 : 4	Cu.m.	2,973.45	13,408.75	
, í		Cu.ft.	84.20	379.75	
iv)	Cement sand 1 : 5	Cu.m.	2,973.45	13,191.60	
		Cu.ft.	84.20	373.60	
		0	0.070.45	40.000 50	
V)	Cement sand 1 : 6	Cu.m.	2,973.45	13,036.50	
		Cu.ft.	84.20	369.20	
vi)	Cement sand 1 : 7	Cu.m.	2,973.45	12,943.45	
¥1)		<b>C</b> 0.111	_,;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;	,0 10.10	

	Description	11	Rat	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
		Cu.ft.	84.20	366.55	
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	2,973.45 84.20	12,850.40 363.95	
e)	Extra for brick masonry in cavity walls in first floor	Cu.m. Cu.ft.	737.95 20.90	745.35 21.10	
f)	Extra for brick masonry in cavity walls in every additional floor above first floor	Cu.m. Cu.ft.	471.10 13.35	475.80 13.45	
11-31	Providing and laying first class hollow burnt brick masonry in walls including scaffolding, raking out joints and curing in ground floor superstructure.				11.70 11.10
-	Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cu.m.	2,379.40	16,063.70	
		Cu.ft.	67.40	454.95	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,379.40 67.40	14,352.85 406.50	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,379.40 67.40	14,184.95 401.75	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,379.40 67.40	14,087.00 398.95	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,379.40 67.40	14,017.00 396.95	
vi)	Cement sand 1 : 7	Cu.m. Cu.ft.	2,379.40 67.40	13,975.05 395.80	
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	2,379.40 67.40	13,933.05 394.60	
	Above 4.5" (115mm) nominal thick brickwork	Cum	2 244 05	15 552 95	
)	Cement sand 1 : 2	Cu.m. Cu.ft.	2,241.05 63.45	15,553.85 440.50	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,241.05 63.45	14,234.90 403.15	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,241.05 63.45	13,980.00 395.90	

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech.
Sr. NO.	Description	Unit	Labour	Composite	Specs.
iv)	Cement sand 1 : 5	Cu.m.	2,241.05	13,831.30	
		Cu.ft.	63.45	391.70	
V)	Cement sand 1 : 6	Cu.m.	2,241.05	13,725.05	
v)		Cu.ft.	63.45	388.70	
		Cu.n.	03.45	300.70	
vi)	Cement sand 1 : 7	Cu.m.	2,241.05	13,661.35	
		Cu.ft.	63.45	386.90	
	(N)				
vii	Cement sand 1:8	Cu.m.	2,241.05	13,597.60	
	Et	Cu.ft.	63.45	385.10	
	AMMU & KAS				
11-32	Providing and laying first class perforated brick masonry in				11.10
-	Upto 4.5" (115 mm) nominal thick brick work	0	0 705 40	45 004 45	
1)	Cement sand 1 : 2	Cu.m.	2,735.42	15,291.45	
		Cu.ft.	77.45	433.05	
ii)	Cement sand 1 : 3	Cu.m.	2,735.42	14,582.85	
,		Cu.ft.	77.45	413.00	
iii)	Cement sand 1 : 4	Cu.m.	2,735.42	14,324.15	
		Cu.ft.	77.45	405.65	
		_			
iv)	Cement sand 1 : 5	Cu.m.	2,735.42	14,173.25	
		Cu.ft.	77.45	401.40	
V)	Cement sand 1 : 6	Cu.m.	2,735.42	14,065.45	
•,		Cu.ft.	77.45	398.35	
		e unu			
vi)	Cement sand 1 : 7	Cu.m.	2,735.42	14,000.80	
		Cu.ft.	77.45	396.50	
vii	Cement sand 1 : 8	Cu.m.	2,735.42	13,936.10	
		Cu.ft.	77.45	394.70	
<b>۲</b>	Above 4.5" (115mm) nominal thick brickwork				
	Cement sand 1 : 2	Cu.m.	2,576.80	14,946.50	
''		Cu.ft.	73.00	423.30	
		Conti	. 0.00	0.00	
ii)	Cement sand 1 : 3	Cu.m.	2,576.80	14,352.85	
		Cu.ft.	73.00	406.50	
iii)	Cement sand 1 : 4	Cu.m.	2,576.80	13,980.85	
		Cu.ft.	73.00	395.95	

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech.	
5r. NO.	Description	Unit	Labour	Composite	Specs.	
iv)	Cement sand 1 : 5	Cu.m. Cu.ft.	2,576.80 73.00	13,763.85 389.80		
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,576.80 73.00	13,608.85 385.40		
vi)	Cement sand 1 : 7	Cu.m. Cu.ft.	2,576.80 73.00	13,515.85 382.80		
vii	Cement sand 1 : 8	Cu.m. Cu.ft.	2,576.80 73.00	13,422.85 380.15		
11-33 a)	Extra for hollow and perforated brick masonry in first floor	Cu.m. Cu.ft.	650.65 18.45	670.15 19.00		
b)	Extra for hollow and perforated brick masonry in every additional floor over first floor.	Cu.m. Cu.ft.	392.95 11.15	404.75 11.45		
11-34	Providing and laying fabric steel reinforcement 1" (25 mm) wire mesh weighing not less than 2 kg/sq.m. including cutting to required shape and size, overlaps, wastage etc. the reinforcement shall be embeded in every third horizontal	Kg. Lb.	22.05 10.00	153.30 69.55	11.15	
11-35	course in basement, plinth and ground floor. Providing and laying mild steel reinforcement bars in brick work including straightening, removing rust, cutting, bending, wastage, overlaps, placing in position, tying with binding wire (cost of binding wire included) in basement, plinth and ground floor.	Ton	9,854.70	90,158.30	11.15	
11-36	Providing and laying hoop iron reinforcement in brick work including straightening, cutting, punching, overlaps, wastage and placing in position including anti-corrosive bitumastic paint two coats in basement, plinth and ground floor.	Kg. Lb.	28.55 12.95	140.40 63.70	11.15	
11-37	Flat iron wall ties size 8" x 3/4" x 1/4" (200 mm x 20 mm x 5 mm) weighing 39.25 kg per sq.m or 200 mm x 20 mm x 4 mm weighing 31.4 kg./ Sq.m.	Kg. Lb.	32.50 14.75	140.95 63.95	11.14.3	
11-38	Providing and placing mild steel reinforcement bars in steining of brick work in wells. Vertical bars are to be placed in two staggered rows and at 10" (250mm) centered in each row including straightening, removing of rust, cutting, bending, binding, wastage, overlaps, placing in position and tying with binding wire upto 5ft. (1.5m) depth or part thereof.	Ton	1,695.55	83,204.85	11.15	
11-39	Providing and placing hoop iron in steining of brick work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Kg. Lb.	32.15 14.60	144.00 65.30	11.15	
11-40 a)	Extra for mild steel bars or hoop iron reinforcement in first	Kg. Lb.	5.70 2.60	6.15 2.80	11.15	

Sr. No.		Description		Rate (Rs.)		Ref. Tech.	
Sr. No	<b>o</b> .	Description	Unit	Labour	Composite	Specs.	
	b)	Providing and placing hoop iron in steining of brick work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Kg. Lb.	3.45 1.55	3.75 1.70		
11-41		Extra for mild steel or hoop iron reinforcement in steining of brickwork in wells for every additional 5 ft (1.5m) depth or part thereof beyond 5ft (1.5m) depth.	Kg. Lb.	6.30 2.85	6.75 3.05	11.15	
11-42		Providing and laying fire brick lining in walls for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19	
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m. Cu.ft.	4,230.15 119.80	16,593.45 469.95		
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire $\cdot$	Cu.m. Cu.ft.	3,636.40 103.00	11,971.55 339.05		
11-43		Providing and laying fire brick lining in arches for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19	
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	4,823.45	20,237.95		
			Cu.ft.	136.60	573.15		
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire	Cu.m.	4,229.70	19,766.75		
		places.	Cu.ft.	119.80	559.80		
11-44		Providing and laying fire brick lining in walls for fire places laid in vitrified fire clay mortar including scaffolding in basement, plinth and ground floor.				11.19	
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire	Cu.m.	4,230.15	16,978.05		
		places.	Cu.ft.	119.80	480.85		
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire	Cu.m.	3,636.40	16,340.45		
		places.	Cu.ft.	103.00	462.75		
11-45		Providing and laying fire brick lining in arches for fire places				11.19	
	a)	4.5" (115 mm) nominal thick fire brick lining in arches of fire	Cu.m. Cu.ft.	4,823.45 136.60	18,165.15 514.45		

Sr. No.		Description	l lmit	Rate (Rs.)		Ref. Tech.
51. NO	).	Description	Unit	Labour	Composite	Specs.
	b)	9" (230 mm) nominal thick fire brick lining in arches of fire	Cu.m.	4,229.70	17,473.95	
	5)		Cu.ft.	119.80	494.85	
			Ou.n.	110.00	+0+.00	
11-46	a)	Extra for first floor over item 11-42 to 11-45	Cu.m.	650.65	670.15	
			Cu.ft.	18.45	19.00	
		(x) man				
	b)	Extra for every additional floor above first floor over item 11-	Cu.m.	392.95	404.75	
		46(a)	Cu.ft.	11.15	11.45	
11-47		Providing and laying reinforced first class burnt bricks set in	Cu.m.	2,671.90	16,817.35	11.70
		cement sand mortar 1:3 in lintel including scaffolding,	Cu.ft.	75.65	476.30	
		fromwork and its removal, curing but excluding the cost of reinforcement in basement, plinth and ground floor.				
		remorcement in basement, plintin and ground hoor.				
11-48		Providing and laying reinforced first class burnt bricks with cement concrete in ribs and on top using screened graded				
		shingle/bajri 3/4" and down gauge, mix not leaner than 1:2:4				
		including formwork and its removal, compacting, curing but				
		excluding the cost of reinforcement in basement and ground floor.				
	a)	R.B. Slab 4.5" nominal thick including 1.5" thick R.C.C. ribs	Cu.m.	3,846.90	14,917.75	
		and 1.5" thick cover on top.	Cu.ft.	108.95	422.50	
	b)	R.B. Slab 6" nominal thick including 1.5" (38mm) thick R.C.C.	Cu.m.	2,671.90	12,782.00	
	5)	ribs and 1.5" thick cover on top.	Cu.ft.	75.65	362.00	
			ound	10.00	002.00	
	c)	R.B. Slab 8" nominal thick including 2" thick R.C. ribs, 1.5"	Cu.m.	2,421.90	11,720.83	
		thick cover on top and 4 brick panel laid in cement sand	Cu.ft.	68.60	331.95	
		mortar 1:3.				
11-49		Providing and laying reinforced first class burnt bricks set in				11.70
		cement sand mortar 1:3 in cantilever slab, sun shade etc.				
		including formwork and its removal curing but excluding the cost of reinforcement in basement and ground floor.				
	a)	3" nominal thick cantilever slab and sun shade etc.	Cu.m.	3,367.31	21,318.16	
	- 1		Cu.ft.	95.35	603.75	
	b)	4.5" (115mm) nominal thick cantilever slab and sun shade	Cu.m.	2,834.20	18,427.91	
			Cu.ft.	80.25	521.90	
11-50		Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in stair case waist slab and landing	Cu.m.	3,877.71	20,651.10	11.70
		of required section including scaffolding and formwork and its				
		removal, curing but excluding the cost of reinforcement in				
		basement and ground floor.				
			Cu.ft.	109.80	584.85	

Sr. No	_	Description	Unit	Rate (Rs.)		Ref. Tech.	
5r. IV	0.	Description	Unit	Labour	Composite	Specs.	
11-51	a)	Extra for R.B. masonry for first floor.	Cu.m.	317.95	409.38		
	u)		Cu.ft.	9.00	11.60		
	b)	Extra for every additional floor above first floor over item 11-	Cu.m.	317.95	327.50		
			Cu.ft.	9.00	9.25		
11-52		Extra labour for profile and flared out walls.	Cu.m.	517.95	533.50		
		E.B. SHIM	Cu.ft.	14.65	15.10		
44 50		Extra labour for pucca brick work in piers and abutment					
11-53		Extra labour for pucca brick work in piers and abutment.					
	a)	Above 10 ft to 20 ft (3 m to 6 m) height	Cu.m.	402.35	414.40		
	- 7		Cu.ft.	11.40	11.75		
	b)	Above 20 ft (6 m) height	Cu.m.	749.20	771.70		
			Cu.ft.	21.20	21.85		
11-54		Extra to face work 4.5" (115 mm) nominal thick using special bricks instead of first class burnt bricks with proper		318.75	350.63		
		ancharage, arrangment as directed by Enigneer incharge.	Cu.ft.	9.05	9.95		
11-55		Extra for dressing or chamfering bricks.					
	a)	Special architectural bricks	% Nos.	862.50	862.50		
	aj		70 1103.	002.50	002.00		
	b)	All other purposes	% Nos.	431.25	431.25		
11-56		Providing and laying ghilafi brick work 13.5" (345mm) nominal					
		thick including scaffolding and raking out joints with 1:5 mortar				11.20	
	a)	Foundation, basement and plinth	Cu.m.	1,740.10	10,130.35		
			Cu.ft.	49.30	286.90		
	b)	Walls in superstructure	Cu.m.	1,833.85	10,224.10		
	5)		Cu.ft.	51.95	289.55		
			2 4.14				
11-57		Providing and laying first class burnt bricks flooring or pitching	Cu.m.	700.00	12,051.80		
		dry bricks laid flat.	Cu.ft.	19.80	341.30	14.80	
11-58		Providing pise wall (mud walling) in superstructure.	Cu.m.	668.75	16,918.75		
			Cu.ft.	18.95	479.15	11.7.2(A)	
				0/5 65	017.00		
11-59		Cleaning bricks dismantled from kacha pacca masonry.	% Nos.	315.00	315.00	4.10	
11-60		Scraping bricks dismantled from pacca masonry.	% Nos.	607.50	607.50	4.10	
11-00		ociaping blicke distriantied north pacea Masolity.	70 1105.	007.00	007.00		

Sr. No.	Description	Unit	Rate (Rs.)		Ref. Tech.
Sr. NO.	Description		Labour	Composite	Specs.
					4.10
11-61	Supplying and filling sand under floor or plugging in wells.with	Cu.m.	209.86	749.51	
	lead upto 800 ft (250m)	Cu.ft.	5.95	21.25	3.8.5
11-62	Chamfering sides of head regulators to increase width.	Cu.m.	831.25	1,204.71	
	(x) star	Cu.ft.	23.55	34.10	
11-63	Replacing Kallar eaten bricks	Each	47.50	76.05	
11-64	Repairing corners of bridges and other hydraulic masonry	Each	475.00	1,045.95	
11-65	Extra labour for drains of bath rooms etc.	R.M.	118.75	118.75	
		R.ft.	36.20	36.20	
11-66	Extra work for Marrow corners.	Each	237.50	275.00	11744(0)
11-67	Extra for first class burnt solid or hollow block or tile masonry	Cu.m.	80.20	94.60	11.7.4.4 (c )
11.07	of any description in any floor or other than building for every 1.50 m. height or part thereof beyond 4.5m.	Cu.ft.	2.25	2.70	11.70
44.00		<b>-</b>	4 740 00	4 7 4 4 9 9	
11-68	Extra for reinforcement in brick work of any description for every 5 ft 1.5m height or part thereof beyond 15 ft or 4.5m.		1,710.00	1,744.20	5.40
		Ton	1,737.45	1,772.20	5.40