C: No	Description	l lm!t	Rate	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
11-1	Providing and laying sundried clay bricks set in mud mortar including scaffolding in foundation and substructure				11.7.2 (i) 11.17
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	2,350.00 66.55	14,522.07 411.25	
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	5,909.70 167.35	13,052.99 369.65	
11-2	Providing and laying first class solid burnt brick masonry set in mud mortar including and raking out joints in foundation and substructure				11.4.1 11.7.2(i) 11.7.4
a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m. Cu.ft.	1,842.65 52.20	17,021.95 482.05	11.7.4
b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	1,367.65 38.75	15,483.20 438.50	
11-3	Providing and laying first class solid burnt brick masonry including scaffolding, raking out joints and curing in foundation and substructure				11.4.1 11.7.2(ii) 11.7.4
a'	Upto 4.5" (115 mm) nominal thick brick work				11.7.4
-	Cement sand 1 : 2	Cu.m. Cu.ft.	1,842.65 52.20	18,980.40 537.55	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	1,842.65 52.20	18,102.15 512.65	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	1,842.65 52.20	17,412.24 493.10	
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	1,842.65 52.20	16,815.94 476.25	
V)	Cement sand 1 : 6	Cu.m. Cu.ft.	1,842.65 52.20	16,331.83 462.55	
V	Cement sand 1 : 7	Cu.m. Cu.ft.	1,842.65 52.20	15,850.27 448.90	
vi	Cement sand 1 : 8	Cu.m. Cu.ft.	1,842.65 52.20	15,372.47 435.35	
b)	Above 4.5" (115mm) nominal thick brickwork				

<u> </u>		11:4	Rate	Ref. Tech.	
Sr. No.	Description	Unit	Labour	Composite	Specs.
į	Cement sand 1:2	Cu.m.	1,367.65	18,380.30	
		Cu.ft.	38.75	520.55	
ii	Cement sand 1:3	Cu.m.	1,367.65	17,312.10	
		Cu.ft.	38.75	490.30	
iii	Cement sand 1:4	Cu.m.	1,367.65	16,473.43	
		Cu.ft.	38.75	466.55	
iv	Cement sand 1 : 5	Cu.m.	1,367.65		
		Cu.ft.	38.75	446.75	
V	Cement sand 1:6	Cu.m.	1,367.65		
	Coment and 4 : 7	Cu.ft.	38.75	429.90	
V	Cement sand 1 : 7	Cu.m.	1,367.65 38.75		
		Cu.ft.	30.75	415.80	
vi	Cement sand 1 : 8	Cu.m.	1,367.65	14,155.30	
VI	Cernent sand 1.0	Cu.ft.	38.75	400.90	
	Se Marie	Cu.it.	30.73	400.30	
11-4	Extra for providing and laying first class burnt brick				11.80
	masonry for arches of any kind of wall including				
	scaffolding, formwork and its removal, raking out joints				
	and curing in basement etc.				
а	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	981.96	3,567.55	
		Cu.ft.	26.70	89.30	
			0.40.50	0.450.00	
b	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	943.53	3,152.39	
		Cu.ft.	27.80	101.05	
11-5	Extra for providing and loving first class tile mesonry				11.80
11-5	Extra for providing and laying first class tile masonry for arches of any kind of walls including scaffolding,				11.90
	formwork and its removal, raking out joints and curing				11.50
	in foundations, basement and plinth.				
_	Linto O" (220 mm) nominal thick tile are a same	C	1 405 07	2.050.70	
a	Upto 9" (230 mm) nominal thick tile masonry	Cu.m.	1,435.27	3,958.72	
		Cu.ft.	40.65	112.10	
b	Above 9" (230 mm) nominal thick tile masonry	Cu.m.	1,356.10	3,603.27	
		Cu.ft.	38.40	102.05	
11-6	Extra for every additional 6 ft (2 m) or part thereof in	Cu.m.	329.40	329.40	11.7.4
	foundation and basement masonry deeper than 6 ft (2	Cu.ft.	9.35	9.35	
	m)				

				Rate	e (Rs.)	Ref. Tech.
Sr. No	ο.	Description	Unit	Labour	Composite	Specs.
11-7		Extra for every additional 5 ft (1.5 m) or part thereof in	Cu.m.	245.00	245.00	11.7.4
		plinth higher than 5 ft (1.5m)	Cu.ft.	6.95	6.95	
					0.00	
11-8		Extra for every additional 6 ft (2m) or part thereof for	Cu.m.	329.40	378.80	11.80
''		arch brick or tile masonry in foundation and basement	Cu.ft.	9.35	10.75	11.90
		masonry deeper than 6ft (2m)	Ou.it.	0.00	10.70	
11-9		Extra for every additional 5 ft (1.5m) or part thereof for		245.00	281.75	11.80
		arch brick or tile masonry in plinth higher than 5ft	Cu.ft.	6.95	8.00	11.90
		(1.5m)				
11-10		Providing and laying sundried clay bricks set in mud				11.7.2(i)
		mortar including scaffolding in ground floor				11.18
		3 3 3				
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	1,465.52	14,195.74	
			Cu.ft.	41.50	402.05	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	1,650.00	8,134.29	
			Cu.ft.	46.75	230.35	
		13				
11-11		Providing and laying first class solid burnt brick				11.4.1
		masonry set in mud mortar including scaffolding,				11.7.2(i)
		raking out joints and curing in ground floor				11.7.4
		WIND & IV				
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	2,292.65	17,160.53	
			Cu.ft.	64.95	486.00	
	b)	Above 4.5" (115mm) nominal thick brickwork	Cu.m.	1,698.74	9,579.84	
			Cu.ft.	48.10	271.30	
11-12		Providing and laying first class solid burnt brick				11.4.1
		masonry including scaffolding, raking out joints and				11.7.2(ii)
	٥)	curing in ground floor superstructure Upto 4.5" (115 mm) nominal thick brick work				11.7.4
	-	Cement sand 1 : 2	Cu.m.	2,292.65	19,766.52	11.7.4
	1)	Cement Sand 1.2	Cu.ft.	64.95	559.80	
			Cu.ii.	04.93	559.60	
	::\	Cement sand 1 : 3	Cum	2 202 65	10 070 02	
	11)	Cement sand 1.3	Cu.m. Cu.ft.	2,292.65		
			Cu.ii.	64.95	534.65	
	iii)	Cement sand 1:4	Cu.m.	2,292.65	18,181.49	
	•		Cu.ft.	64.95	514.90	
		Compart count 4 v 5	C	0 000 05	47.504.00	
	IV	Cement sand 1 : 5	Cu.m.	2,292.65		
			Cu.ft.	64.95	498.00	

				Date	e (Rs.)	Ref. Tech.
Sr. No) .	Description	Unit	Labour	Composite	Specs.
				Labour	Composite	оресз.
	v)	Cement sand 1 : 6	Cu.m.	2,292.65	17,126.01	
	,		Cu.ft.	64.95	485.00	
	vi	Cement sand 1 : 7	Cu.m.	2,292.65	16,648.40	
			Cu.ft.	64.95	471.50	
	vii	Cement sand 1 : 8	Cu.m.	2,292.65		
			Cu.ft.	64.95	458.20	
	b)	Above 4.5" (115mm) nominal thick brickwork				
	-	Cement sand 1 : 2	Cum	1 017 65	10.047.44	
	1)	Cement sand 1.2	Cu.m. Cu.ft.	1,817.65 51.50	19,047.41 539.45	
			Ou.it.	01.00	000.40	
	ii)	Cement sand 1:3	Cu.m.	1,817.65	17,973.25	
			Cu.ft.	51.50	509.00	
		(x) mar				
	iii)	Cement sand 1:4	Cu.m.	1,817.65		
			Cu.ft.	51.50	485.10	
	iv	Cement sand 1:5	Cu.m.	1,817.65	16,469.24	
		AND SKASHIM	Cu.ft.	51.50	466.40	
		SAMMU & WA				
	v)	Cement sand 1 : 6	Cu.m.	1,817.65	15,865.61	
			Cu.ft.	51.50	449.30	
	:	Cement sand 1 : 7	Cum	1 017 65	15 206 04	
	VI	Cement sand 1.7	Cu.m. Cu.ft.	1,817.65 51.50	15,386.84 435.75	
			Ou.it.	31.50	400.70	
	vii	Cement sand 1:8	Cu.m.	1,817.65	14,904.61	
			Cu.ft.	51.50	422.10	
11-13		Extra for providing and laying first class burnt brick masonry for arches of any kind of wall including				11.80
		scaffolding, formwork and its removal, raking out joints				
		and curing in ground floor superstructures.				
	a)	Upto 4.5" (115 mm) nominal thick brick work	Cu.m.	334.80	3,023.22	
			Cu.ft.	9.50	85.60	
	P.	Above 4 F" (44Fmm) nominal thick bridges at	Cu	202.20	0.750.00	
	D)	Above 4.5" (115mm) nominal thick brickwork	Cu.m. Cu.ft.	293.30 8.30	2,756.63 78.05	
			Ou.it.	0.50	70.00	
11-14		Extra for providing and laying first class tile masonry				11.80
		for arches of any kind of walls including scaffolding,				11.90
		formwork and its removal, raking out joints and curing in ground floor superstructures.				
		in ground hour superstructures.				

Sr. No.	Description		Rate	e (Rs.)	Ref. Tech.
31. NO.	Description	Unit	Labour	Composite	Specs.
a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	4,093.30 115.90	6,829.23 168.80	
b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	3,618.30 102.45	5,960.90 193.40	
11-15	Extra for masonry in pillars and columns in foundation				11.18
a)	Rectangular or square shape	Cu.m. Cu.ft.	1,255.80 35.55	1,708.82 48.40	
b)	Round shape	Cu.m. Cu.ft.	2,787.05 78.95	3,523.10 99.80	
11-16	Extra for masonry in pillars and cloumns in ground floor superstructure				11.7.4
a)	Rectangular or square shape	Cu.m. Cu.ft.	1,343.00 38.05	2,546.10 72.10	
b)	Round shape	Cu.m. Cu.ft.	2,596.72 73.55	5,034.00 142.55	
11-17	Extra for masonry of any description in steps.	Cu.m. Cu.ft.	805.46 22.80	805.46 22.80	11.17.4
11-18	Extra for masonry of any description for bonding old and new masonry including making recesses as required (New masonry inserted in old masonry to be measured)	Cu.m. Cu.ft.	330.85 9.35	473.15 13.40	11.11
11-19	Providing and laying first class burnt brick honey comb masonry including scaffolding, raking out joints where required and curing in ground floor superstructure (opening not to be deducted for the purpose of measurement).				11.10
	Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cu.m. Cu.ft.	1,436.70 40.70	15,243.70 431.70	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	1,436.70 40.70	14,910.05 422.25	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	1,436.70 40.70	14,689.45 416.00	

			Rati	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	
			Labour	Composite	орссэ.
, i.	Cement sand 1 : 5	Cu.m.	1,436.70	14,560.80	
1\	Cement sand 1.3	Cu.ft.	40.70	412.35	
		Cu.it.	40.70	412.00	
v,	Cement sand 1 : 6	Cu.m.	1,436.70	14,468.90	
		Cu.ft.	40.70	409.75	
v	Cement sand 1:7	Cu.m.	1,436.70	14,413.75	
		Cu.ft.	40.70	408.20	
vi	Cement sand 1:8	Cu.m.	1,436.70	14,358.60	
		Cu.ft.	40.70	406.65	
b)	Above 4.5" (115mm) nominal thick brickwork				
į i	Cement sand 1:2	Cu.m.	1,405.45	8,393.55	
		Cu.ft.	39.80	237.70	
ii)	Cement sand 1:3	Cu.m.	1,405.45	7,922.00	
		Cu.ft.	39.80	224.35	
iii)	Cement sand 1:4	Cu.m.	1,405.45		
	E GHAN	Cu.ft.	39.80	214.20	
	AMMU & KASHMI				
i۱	Cement sand 1 : 5	Cu.m.	1,405.45		
		Cu.ft.	39.80	205.30	
		O	4 405 45	0.044.04	
V,	Cement sand 1:6	Cu.m.	1,405.45		
		Cu.ft.	39.80	195.75	
,,	Cement sand 1:7	Cu.m.	1,405.45	6,673.34	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Cement sand 1.7	Cu.ft.	39.80	189.00	
		Ou.it.	J9.00	109.00	
vi	Cement sand 1 : 8	Cu.m.	1,405.45	6,396.78	
"		Cu.ft.	39.80	181.15	
		Juli.	30.00	.51.10	
11-20	Extra for providing and laying first class burnt brick				11.12
	masonry architrave of required shape of any kind of				
	walls including cutting bricks to required shape,				
	scaffolding, raking out joints and curing in ground floor				
	superstructure.				
,		0	4 000 00	4.000.45	
l a	Upto 9" (230 mm) nominal thick brick work	Cu.m.	1,888.90		
		Cu.ft.	53.50	130.85	
L.	Above 12 F" (24F mm) nominal thick brick work	Cu	1 050 00	2.762.62	
, D	Above 13.5" (345 mm) nominal thick brick work	Cu.m. Cu.ft.	1,058.09 29.95	2,763.63 78.25	
		Cu.it.	23.30	70.20	
l	I		I	I	ı

Sr. No		Deceriation	11:5!4	Rate	e (Rs.)	Ref. Tech.
Sr. No).	Description	Unit	Labour	Composite	Specs.
11-21		Extra for providing and laying first class burnt tile masonry architrave of required shape of any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.80 11.12
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	2,137.70 60.55	3,648.13 103.30	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,974.09 55.90	3,230.14 91.50	
11-22		Extra for providing and laying first class burnt brick masonry coping of required shape any kind of walls including cutting bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m. Cu.ft.	1,099.50 31.15	3,075.65 87.10	
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m. Cu.ft.	1,010.56 28.60	2,600.65 73.65	
11-23		Extra for providing and laying first class burnt tile masonry coping of required shape any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure.				11.17
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,855.00 52.55	8,247.50 233.55	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,730.63 49.00	7,537.60 213.45	
11-24		Extra for providing and laying first class burnt brick masonry cornice, moulding, string course and drip course of required shape in any kind of walls including cutting of bricks to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.12
	a)	Upto 9" (230 mm) nominal thick brick work	Cu.m. Cu.ft.	871.59 24.70	1,830.34 51.85	
	b)	Above 13.5" (345 mm) nominal thick brick work	Cu.m. Cu.ft.	777.79 22.05	1,711.13 48.45	

C:: N		December 1	11:4	Rate	e (Rs.)	Ref. Tech.
Sr. No	o. 	Description	Unit	Labour	Composite	Specs.
11-25		Extra for providing and laying first class burnt tile masonry cornice, moulding, barges, string course and drip course of required shape in any kind of walls including cutting tiles to required shape, scaffolding, raking out joints and curing in ground floor superstructure				11.17
	a)	Upto 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,855.00 52.55	6,032.17 170.85	
	b)	Above 9" (230 mm) nominal thick tile masonry	Cu.m. Cu.ft.	1,225.95 34.70	4,990.84 141.35	
11-26	a)	Extra for brick masonry in first floor	Cu.m. Cu.ft.	650.65 18.45	670.15 19.00	11.17
	b)	Extra for brick or tile masonry in every additional floor over first floor.	Cu.m.	392.95	404.75	
			Cu.ft.	11.15	11.45	
11-27	a)	Extra for brick or tile masonry arches in first floor.	Cu.m. Cu.ft.	819.40 23.20	937.35 26.55	11.17
	b)	Extra for brick or tile masonry in every additional floor over first floor	Cu.m. Cu.ft.	561.70 15.90	642.60 18.20	11.17
11-28	a)	Extra for honey comb masonry in first floor	Cu.m. Cu.ft.	481.90 13.65	496.35 14.05	11.10
	b)	Extra for honey comb masonry in every additional floor over first floor.	Cu.m.	392.95	404.75	
11-29		Providing and laying first class brick masonry in steining of walls including scaffolding and curing upto 10 ft (3 m) depth.		11.15	11.45	11.70
		Upto 13.5" (345 mm) nominal thick brick masonry Cement sand 1 : 2	Cu.m. Cu.ft.	2,373.90 67.25	15,095.06 427.50	
	ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,373.90 67.25	14,386.57 407.45	
	iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,373.90 67.25	13,922.45 394.30	
	iv	Cement sand 1 : 5	Cu.m. Cu.ft.	2,373.90 67.25	13,419.05 380.05	

			Date	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
			Labour	Composite	оросо.
v)	Cement sand 1 : 6	Cu.m.	2,373.90	12,916.62	
		Cu.ft.	67.25	365.80	
V	Cement sand 1 : 7	Cu.m.	2,373.90	12,918.23	
		Cu.ft.	67.25	365.85	
vi	Cement sand 1:8	Cu.m.	2,373.90		
		Cu.ft.	67.25	355.45	
	Al 40 5 (045 mm)				
-	Above 13.5" (345 mm) nominal thick brick masonry	C	1 011 10	10 710 00	
1)	Cement sand 1 : 2	Cu.m. Cu.ft.	1,811.40 51.30	13,742.00 389.20	
		Cu.ii.	51.50	309.20	
ii)	Cement sand 1 : 3	Cu.m.	1,811.40	13,159.41	
"	Coment sand 1.0	Cu.ft.	51.30	372.70	
		• • • • • • • • • • • • • • • • • • • •	000	0.2	
iii)	Cement sand 1:4	Cu.m.	1,811.40	12,820.14	
ĺ		Cu.ft.	51.30	363.05	
	(a)				
iv	Cement sand 1:5	Cu.m.	1,811.40	12,622.24	
	Eg Jimir	Cu.ft.	51.30	357.45	
	Coment cond 1 : 6				
v)	Cement sand 1 : 6	Cu.m.			
		Cu.ft.	51.30	353.45	
	Company cond 4 : 7	O	4 044 40	40.000.07	
V	Cement sand 1 : 7	Cu.m.	1,811.40 51.30	*	
		Cu.ft.	51.30	351.05	
vi	Cement sand 1 : 8	Cu.m.	1,811.40	12,311.24	
V 1	Coment sand 1.0	Cu.ft.	51.30	348.65	
		-	01.00	0.0.00	
c)	Extra for every additional 5 ft (1.5 m) depth or part	Cu.m.	301.25	310.30	
ĺ	thereof for brick masonry in steining of walls.	Cu.ft.	8.55	8.80	
11-30	Providing and laying first class burnt brick masonry				11.14
	cavity walls bonded with wall ties of approved design				
	at required horizontal and vertical spacings including scaffolding, raking out joints and curing in ground floor				
	superstructure but excluding the cost of wall ties (No				
	deduction will be made from the measurement for				
	cavity in the wall).				
a)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5"				
	(115 mm) wall width on either side.				
i)	Cement sand 1 : 2	Cu.m.	2,885.95		
		Cu.ft.	81.75	491.95	

	.		Rat	Rate (Rs.)			
r. No.	Description	Unit	Labour	Composite			
ii)	Cement sand 1:3	Cu.m.	2,885.95	16,867.30			
		Cu.ft.	81.75	477.70			
iii)	Cement sand 1 : 4	Cu.m.	2,885.95	16,534.30			
		Cu.ft.	81.75	468.25			
				40.040.05			
IV	Cement sand 1 : 5	Cu.m.	2,885.95	16,340.05			
		Cu.ft.	81.75	462.75			
v)	Cement sand 1 : 6	Cu.m.	2,885.95	16,201.30			
		Cu.ft.	81.75	458.85			
vi	Cement sand 1:7	Cu.m.	2,885.95	16,118.05			
		Cu.ft.	81.75	456.45			
	(*) [292]						
VII	Cement sand 1 : 8	Cu.m.	2,885.95	16,034.80			
L \	2" to 2" (50 mags to 75 mags) begins a solity and 4.5"	Cu.ft.	81.75	454.10			
D)	2" to 3" (50 mm to 75 mm) nominal cavity and 4.5" (115 mm) wall width on one side and 9" (230 mm) wall						
	width on the other side.						
:\	Cement sand 1 : 2	Cu.m.	3,060.95	18,646.70			
1)	Cement sand 1.2	Cu.m.	86.70	528.10			
		Cu.it.	00.70	320.10			
ii)	Cement sand 1 : 3	Cu.m.	3,060.95	18,025.10			
,		Cu.ft.	86.70	510.50			
iii)	Cement sand 1 : 4	Cu.m.	3,060.95	17,614.20			
		Cu.ft.	86.70	498.85			
iv	Cement sand 1 : 5	Cu.m.	3,060.95				
		Cu.ft.	86.70	492.05			
W	Cement sand 1 : 6	Cu.m.	3,060.95	17,203.30			
٧)	Cement sand 1.0	Cu.ft.	86.70	487.20			
		Cu.it.	00.70	407.20			
vi	Cement sand 1:7	Cu.m.	3,060.95	17,100.60			
-		Cu.ft.	86.70	484.30			
vii	Cement sand 1 : 8	Cu.m.	3,060.95	16,997.85			
		Cu.ft.	86.70	481.40			
c)	2" to 3" (50 mm to 75 mm) nominal cavity and 9" (230						
	mm) wall width on either side.						
i)	Cement sand 1 : 2	Cu.m.	2,735.95	19,045.40			
		Cu.ft.	77.50	539.40			

Sr. No.	Description	Unit	Rate	e (Rs.)	Ref. Tech
Sr. NO.	Description	Unit	Labour	Composite	Specs.
::\	0	0	0.705.05	40 440 00	
II)	Cement sand 1 : 3	Cu.m.	2,735.95		
		Cu.ft.	77.50	514.00	
iii)	Cement sand 1 : 4	Cu.m.	2,735.95	17,557.90	
,	Comonicound 1. 1	Cu.ft.	77.50	497.25	
iv	Cement sand 1 : 5	Cu.m.	2,735.95	15,513.10	
		Cu.ft.	77.50	439.35	
		_			
v)	Cement sand 1 : 6	Cu.m.			
		Cu.ft.	77.50	480.50	
vi	Cement sand 1 : 7	Cu.m.	2,735.95	16,817.90	
VI	Cement Sand 1.7	Cu.ft.	77.50	476.30	
		Cu.it.	77.30	470.30	
vii	Cement sand 1 : 8	Cu.m.	2,735.95	16,669.90	
• • • •		Cu.ft.	77.50	472.10	
	(Ma)	Ou.it.	77.00	172.10	
d)	2" to 3" (50mm to 75mm) nominal cavity and 4.5"				
۵,	(115mm) wall width on one side and 13.5" (345mm)				
	wall width on other side. Cement sand 1:2				
i)	Cement sand 1:2	Cu.m.	2,973.45		
		Cu.ft.	84.20	542.35	
;;)	Cement sand 1 : 3	Cu.m.	2,973.45	18,465.80	
11)	Cement Sand 1.5	Cu.ft.	84.20	522.95	
		Cu.ii.	04.20	522.95	
iii)	Cement sand 1 : 4	Cu.m.	2,973.45	18,013.40	
ĺ		Cu.ft.	84.20	510.15	
iv	Cement sand 1 : 5	Cu.m.	2,973.45	17,749.45	
		Cu.ft.	84.20	502.65	
,	0	•	0.070.45	47 500 05	
V)	Cement sand 1 : 6	Cu.m.	2,973.45		
		Cu.ft.	84.20	497.35	
vi	Cement sand 1 : 7	Cu.m.	2,973.45	17,447.85	
VI	Coment Sana 1 . 7	Cu.ft.	84.20	494.15	
		Ou.it.	04.20	TOT. 10	
vii	Cement sand 1 : 8	Cu.m.	2,973.45	17,334.75	
		Cu.ft.	84.20	490.95	
e)	Extra for brick masonry in cavity walls in first floor	Cu.m.	737.95	745.35	
		Cu.ft.	20.90	21.10	
	•		-	-	-

_	_		Rate (Rs.)		Ref. Tech.
Sr. No.	Description	Unit	Labour	Composite	Specs.
f)	Extra for brick masonry in cavity walls in every additional floor above first floor	Cu.m. Cu.ft.	471.10 13.35	475.80 13.45	
11-31	Providing and laying first class hollow burnt brick masonry in walls including scaffolding, raking out joints and curing in ground floor superstructure.				11.70 11.10
-	Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cu.m. Cu.ft.	2,379.40 67.40	21,988.00 622.70	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,379.40 67.40	20,091.00 569.00	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,379.40 67.40	19,886.90 563.20	
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	2,379.40 67.40	19,767.85 559.85	
v)	Cement sand 1:6	Cu.m. Cu.ft.	2,379.40 67.40	19,682.80 557.45	
V	Cement sand 1 : 7	Cu.m. Cu.ft.	2,379.40 67.40	19,631.80 556.00	
vi	Cement sand 1 : 8	Cu.m. Cu.ft.	2,379.40 67.40	19,580.75 554.55	
-	Above 4.5" (115mm) nominal thick brickwork Cement sand 1 : 2	Cu.m. Cu.ft.	2,241.05 63.45	21,390.05 605.80	
ii)	Cement sand 1 : 3	Cu.m. Cu.ft.	2,241.05 63.45	19,788.50 560.40	
iii)	Cement sand 1 : 4	Cu.m. Cu.ft.	2,241.05 63.45	19,478.65 551.65	
iv	Cement sand 1 : 5	Cu.m. Cu.ft.	2,241.05 63.45	19,297.95 546.55	
v)	Cement sand 1 : 6	Cu.m. Cu.ft.	2,241.05 63.45	19,168.85 542.85	

_			Rate	e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit	Rate (Rs.) Labour Composite		-1
			Labour	Composite	оросо.
vi	Cement sand 1 : 7	Cu.m.	2,241.05	19,091.40	
		Cu.ft.	63.45	540.70	
vii	Cement sand 1:8	Cu.m.	2,241.05	19,013.95	
		Cu.ft.	63.45	538.50	
1-32	Providing and laying first class perforated brick				11.10
- \	Hate 4 Ell (44 E ann) ann in deil in heide and				
	Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 2	Cum	2 725 42	21 049 55	
1)	Cement sand 1:2	Cu.m. Cu.ft.	2,735.42 77.45	21,048.55 596.10	
		Cu.it.	77.43	390.10	
ii)	Cement sand 1 : 3	Cu.m.	2,735.42	20,053.20	
,		Cu.ft.	77.45	567.90	
iii)	Cement sand 1:4	Cu.m.	2,735.42	19,738.80	
		Cu.ft.	77.45	559.00	
	Ser Section				
iv	Cement sand 1 : 5	Cu.m.	2,735.42		
	AMMU & KASHMIN	Cu.ft.	77.45	553.80	
v)	Cement sand 1 : 6	Cu.m.	2,735.42	19,424.35	
• ,	Comon cana 1.0	Cu.ft.	77.45	550.10	
vi	Cement sand 1:7	Cu.m.	2,735.42	19,345.75	
		Cu.ft.	77.45	547.90	
VII	Cement sand 1 : 8	Cu.m.			
		Cu.ft.	77.45	545.65	
b)	Above 4.5" (115mm) nominal thick brickwork				
,	,				
i)	Cement sand 1 : 2	Cu.m.	2,576.80	20,538.85	
		Cu.ft.	73.00	581.65	
		•	0.570.00	40 500 00	
11)	Cement sand 1:3	Cu.m.	2,576.80	19,532.80	
		Cu.ft.	73.00	553.20	
iii)	Cement sand 1 : 4	Cu.m.	2,576.80	19,080.70	
"")	Someth Sand 1. 1	Cu.ft.	73.00	540.40	
			. 5.50	2.0.10	
iv	Cement sand 1 : 5	Cu.m.	2,576.80	18,816.95	
		Cu.ft.	73.00	532.90	
	ı		1	l .	•

			Rate (Rs.)		Ref. Tech.	
Sr. N	ο.	Description	Unit	Labour	Composite	
						•
	v)	Cement sand 1 : 6	Cu.m.	2,576.80	18,628.55	
	,		Cu.ft.	73.00	527.55	
	vi	Cement sand 1 : 7	Cu.m.	2,576.80	18,515.55	
			Cu.ft.	73.00	524.35	
	vii	Cement sand 1:8	Cu.m.	2,576.80	18,402.50	
			Cu.ft.	73.00	521.15	
11-33	a)	Extra for hollow and perforated brick masonry in first	Cu.m.	650.65	670.15	
		floor				
			Cu.ft.	18.45	19.00	
	b)	Extra for hollow and perforated brick masonry in every	Cu.m.	392.95	404.75	
		additional floor over first floor.	Cu.ft.	11.15	11.45	
11-34		Providing and laying fabric steel reinforcement 1" (25	Kg.	22.05	168.15	11.15
		mm) wire mesh weighing not less than 2 kg/sq.m.	Lb.	10.00	76.25	
		including cutting to required shape and size, overlaps, wastage etc. the reinforcement shall be embeded in				
		every third horizontal course in basement, plinth and				
		ground floor				
11-35		Providing and laying mild steel reinforcement bars in	M.T.	9,854.70	99,248.20	11.15
		brick work including straightening, removing rust,				
		cutting, bending, wastage, overlaps, placing in				
		position, tying with binding wire (cost of binding wire				
		included) in basement, plinth and ground floor.				
11-36		Providing and laying hoop iron reinforcement in brick	Kg.	28.55	153.05	11.15
		work including straightening, cutting, punching,	Lb.	12.95	69.40	
		overlaps, wastage and placing in position including				
		anti-corrosive bitumastic paint two coats in basement,				
		plinth and ground floor.				
11-37		Flat iron wall ties size 8" x 3/4" x 1/4" (200 mm x 20	Kg.	32.50	153.20	11.14.3
		mm x 5 mm) weighing 39.25 kg per sq.m or 200 mm x	Lb.	14.75	69.50	
		20 mm x 4 mm weighing 31.4 kg./ Sq.m.				
11-38		Providing and placing mild steel reinforcement bars in				11.15
11-30		steining of brick work in wells. Vertical bars are to be	M.T.	1,695.55	92,440.65	
		placed in two staggered rows and at 10" (250mm)	IVI. I .	1,000.00	32,440.00	
		centered in each row including straightening, removing				
		of rust, cutting, bending, binding, wastage, overlaps,				
		placing in position and tying with binding wire upto 5ft. (1.5m) depth or part thereof.				
		(1.5m) deput or part increor.				
11-39		Providing and placing hoop iron in steining of brick	Kg.	32.15	156.65	11.15
11-39		work in wells including cutting, straightening, bending,	kg. Lb.	14.60	71.05	11.13
		wastage, overlaps and placing in position upto 5 ft.(1.5	LU.	17.00	7 1.00	
		m) depth or part thereof.				
J				l	l	

				Rate	e (Rs.)	Ref. Tech.	
Sr. No	Э.	Description	Unit	Labour	Composite	Specs.	
				<u> Labour</u>	Composito		
11-40	a)	Extra for mild steel bars or hoop iron reinforcement in first floor.	Kg.	5.70	6.15	11.15	
		mst noor.	Lb.	2.60	2.80		
	b)	Providing and placing hoop iron in steining of brick work in wells including cutting, straightening, bending, wastage, overlaps and placing in position upto 5 ft.(1.5 m) depth or part thereof.	Kg. Lb.	3.45 1.55	3.75 1.70		
11-41		Extra for mild steel or hoop iron reinforcement in steining of brickwork in wells for every additional 5 ft (1.5m) depth or part thereof beyond 5ft (1.5m) depth.		6.30 2.85	6.75 3.05	11.15	
11-42		Providing and laying fire brick lining in walls for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor superstructures.				11.19	
	a)	4.5" (115 mm) nominal thick fire brick lining in walls of fire places.	Cu.m.	4,230.15	22,406.60		
			Cu.ft.	119.80	634.55		
	b)	9" (230 mm) nominal thick fire brick lining in walls of fire places.	Cu.m.	3,636.40	15,752.80		
			Cu.ft.	103.00	446.15		
11-43		Providing and laying fire brick lining in arches for fire places laid in mortar of high alumina cement and fine aggregate of crushed fire brick 1:2 including scaffolding in basement, plinth and ground floor				11.19	
	a)	4.5" (115 mm) nominal thick fire brick lining in arches	Cu.m.	4,823.45	26,412.55		
		of fire places.	Cu.ft.	136.60	748.00		
	b)	9" (230 mm) nominal thick fire brick lining in arches of	Cu.m.	4,229.70	25,965.80		
		fire places.	Cu.ft.	119.80	735.35		
11-44		Providing and laying fire brick lining in walls for fire places laid in vitrified fire clay mortar including scaffolding in basement, plinth and ground floor.				11.19	
	-	4.5" (115 mm) nominal thick fire brick lining in walls of fire places.	Cu.m.	4,230.15	22,872.85		

			Rati	Poor Ref. Tech.	
Sr. No.	Description	Unit	Labour	e (Rs.)	Specs.
			Labour	Composite	opecs.
		Cu.ft.	119.80	647.75	
b	9" (230 mm) nominal thick fire brick lining in walls of fire places.	Cu.m.	3,636.40	22,228.60	
		Cu.ft.	103.00	629.55	
11-45	Providing and laying fire brick lining in arches for fire places with vitrified fire clay mortar including scaffolding, formwork and its removal in basement, plinth & ground floor.				11.19
a	4.5" (115 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	4,823.45	24,328.25	
	of the places.	Cu.ft.	136.60	689.00	
b	9" (230 mm) nominal thick fire brick lining in arches of fire places.	Cu.m.	4,229.70	23,606.30	
	THE STATE OF THE S	Cu.ft.	119.80	668.55	
11-46 a	Extra for first floor over item 11-42 to 11-45	Cu.m. Cu.ft.	650.65 18.45	670.15 19.00	
b	Extra for every additional floor above first floor over item 11-46(a)	Cu.m.	392.95	404.75	
		Cu.ft.	11.15	11.45	
11-47	Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in lintel including scaffolding, fromwork and its removal, curing but excluding the cost of reinforcement in basement, plinth and ground floor.	Cu.ft.	2,671.90 75.65	21,446.45 607.40	11.70
11-48	Providing and laying reinforced first class burnt bricks with cement concrete in ribs and on top using screened graded shingle/bajri 3/4" and down gauge, mix not leaner than 1:2:4 including formwork and its removal, compacting, curing but excluding the cost of reinforcement in basement and ground floor.				
а	R.B. Slab 4.5" nominal thick including 1.5" thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	3,846.90 108.95	16,971.15 480.65	
b	R.B. Slab 6" nominal thick including 1.5" (38mm) thick R.C.C. ribs and 1.5" thick cover on top.	Cu.m. Cu.ft.	2,671.90 75.65	15,564.69 440.80	
c	R.B. Slab 8" nominal thick including 2" thick R.C. ribs, 1.5" thick cover on top and 4 brick panel laid in cement sand mortar 1:3.	Cu.m. Cu.ft.	2,421.90 68.60	14,619.86 414.05	

Cr No	Deparintion	Rate (Rs.)		e (Rs.)	Ref. Tech.
Sr. No.	Description	Unit		Composite	Specs.
11-49	Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in cantilever slab, sun shade etc. including formwork and its removal curing but excluding the cost of reinforcement in basement and ground floor.				11.70
a)	3" nominal thick cantilever slab and sun shade etc.	Cu.m. Cu.ft.	3,367.31 95.35	25,350.77 717.95	
b)	4.5" (115mm) nominal thick cantilever slab and sun	Cu.m. Cu.ft.	2,834.20 80.25	22,482.91 636.75	
11-50	Providing and laying reinforced first class burnt bricks set in cement sand mortar 1:3 in stair case waist slab and landing of required section including scaffolding and formwork and its removal, curing but excluding the cost of reinforcement in basement and ground floor	Cu.m.	3,877.71	25,866.95 732.55	11.70
11-51 a)	Extra for R.B. masonry for first floor.	Cu.m. Cu.ft.	317.95 9.00	409.38 11.60	
b)	Extra for every additional floor above first floor over item 11-46(a)	Cu.m.	317.95 9.00	327.50 9.25	
11-52	Extra labour for profile and flared out walls.	Cu.m. Cu.ft.	517.95 14.65	533.50 15.10	
11-53	Extra labour for pucca brick work in piers and abutment				
a)	Above 10 ft to 20 ft (3 m to 6 m) height	Cu.m. Cu.ft.	402.35 11.40	414.40 11.75	
b)	Above 20 ft (6 m) height	Cu.m. Cu.ft.	749.20 21.20	771.70 21.85	
11-54	Extra to face work 4.5" (115 mm) nominal thick using special bricks instead of first class burnt bricks with proper ancharage, arrangment as directed by Enigneer incharge.	Cu.m. Cu.ft.	127.50 3.60	140.25 3.95	
11-55	Extra for dressing or chamfering bricks.				

Sr. No.	Description	Unit	Rat	e (Rs.)	Ref. Tech.
Sr. NO.	Description	Onit	Labour	Composite	Specs.
ā) Special architectural bricks	% Nos.	862.50	862.50	
k) All other purposes	% Nos.	431.25	431.25	
11-56	Providing and laying ghilafi brick work 13.5" (345mm) nominal thick including scaffolding and raking out joints with 1:5 mortar				11.20
a) Foundation, basement and plinth	Cu.m. Cu.ft.	1,740.10 49.30	13,348.05 378.00	
t) Walls in superstructure	Cu.m. Cu.ft.	1,833.85 51.95	13,441.80 380.70	
11-57	Providing and laying first class burnt bricks flooring or pitching dry bricks laid flat.	Cu.m. Cu.ft.	700.00 19.80	15,835.70 448.50	14.80
11-58	Providing pise wall (mud walling) in superstructure.	Cu.m. Cu.ft.	668.75 18.95	16,918.75 479.15	11.7.2(A)
11-59	Cleaning bricks dismantled from kacha pacca masonry.	% Nos.	315.00	315.00	
11-60	Scraping bricks dismantled from pacca masonry.	% Nos.	607.50	607.50	4.10
11-61	Supplying and filling sand under floor or plugging in wells.with lead upto 800 ft (250m)	Cu.m. Cu.ft.	363.14 10.30	1,296.92 36.75	3.8.5
11-62	Chamfering sides of head regulators to increase width.	Cu.m. Cu.ft.	831.25 23.55	1,204.71 34.10	
11-63	Replacing Kallar eaten bricks	Each	47.50	90.65	
11-64	Repairing corners of bridges and other hydraulic masonry works.	Each	475.00	1,337.50	
11-65	Extra labour for drains of bath rooms etc.	R.M. R.ft.	118.75 36.20	118.75 36.20	
11-66	Extra work for Marrow corners.	Each	237.50	287.50	11.7.4.4 (c)
11-67	Extra for first class burnt solid or hollow block or tile masonry of any description in any floor or other than building for every 1.50 m. height or part thereof beyond 4.5m.	Cu.ft.	80.20 2.25	94.60 2.70	11.70
11-68	Extra for reinforcement in brick work of any description for every 5 ft 1.5m height or part thereof beyond 15 ft or 4.5m.		1,710.00 1,737.45	1,744.20 1,772.20	5.40

Sr. No. Description	Description	Unit	Rate (Rs.)		Ref. Tech.
	Oilit	Labour	Composite	Specs.	

